30-045-20529

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

											Well		
Operator	BURLINGTON RESOURCES OIL & GAS CO.						Lease	ease WILMER CANYON			No.	1	
Location													
of Well:	Unit	M	Sect NAME O	24 F RESERVOI	Twp. R OR POOI	032N	Rge T	008W YPE OF PROD. (Oil or Gas)	County SA METHOD (Flow or A			OD. MEDIUM Γbg. or Csg.)	
Upper Completion FRUITLAND/PICTURE				ED CLIFFS	•			Gas	Flow		Tubing		
Lower Completion	MESAVERDE						Gas		Flow	Flow		Tubing	
					PRE-F	LOW SHUT-I	N PRESS	URE DATA					
Upper Completion				Length of time shut-in 72 Hours			SI press. psig Stabil 519			abilized? (Y	es or No)	l	
Lower Completion 07/07/2000		144 Hours 343					•						
						FLOW T	EST NO.	1					
Commenced at (hour,date)*				0	07/10/2000			Zone producing (Upper or Lower) UPROD. ZONE					
TIME (hour.date)	LAPSED TIME SINCE*			PRESSURE Upper Completion Lower Comp			pletion				REMARKS		
07/11/2000		96	Hours	35	58	350							
07/13/2000		144	Hours	28	30	352							
								15 05 El B	22 23 24 25 3				
								Se PA	Ul A				
								£ 0,00	E1200)A			
								1818 1818 1818 1818 1818 1818 1818 181	ono				
Production rat	te during	test						1681	Q 6 7 6 70			•	
Oil:		BOF	D based on		Bbls. ir	1	Hours		Grav.		GOR		
Gas:				MCFPD; T	ested thru (Orifice or Met	er):						
					MID-T	TEST SHUT-D	N PRESS	URE DATA					
Upper Completion	Hour, date shut-in		Length of time shut-in			•	ress. psig	Sta	Stabilized? (Yes or No)				
Lower Completion	Hour, date shut-in			Length of time shut-in			SIp	SI press. psig Stabilized?			es or No)	
8587101 369	€												

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, da	ate)**		Zone producing (Upper or Lower):				
TIME (hour, date)	LAPSED TIME	PRESSURE		PROD. ZONE	REMARKS		
	SINCE **	Upper Completion	Lower Completion	TEMP.	REMARNS		
!							
	1		<u> </u>				
Production rate du	ring test						
Oil:	BC	PD based on	Bbls. in	Hours	Grav. GOR		
Gae:		MCEDI	Or Tastad they (Or	ifice or Meter):			
Gas.		WICHTI	o. Tested tilla (Of.	mice of Weter).			
Remarks:							
I hereby certify that	it the information her	ein contained is true	e and complete to t	he best of my knowledg	ee.		
Approved	JUL 2 5 20	100	0	Operator Burlingto	on Resources		
			9	Operator Durinigte	1 '		
New Mexico O	il Conservation Divi	sion		By Whore &	lows		
QPI@	nal signed by Ci	HAPLIE T. PETRIMI		- - 101-44			
			Title Operations Associate				
ספיטו	OIL & GAS INSPE	Clow, Die					
Title	· · · · · · ·			Date Monday, July 17, 2000			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1 A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- $5. \quad Following \ completion \ of \ Flow \ Test \ No. \ 1, \ the \ well \ shall \ again \ be \ shut-in, in \ accordance \ with \ Paragraph \ 3 \ above.$
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).