

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Wildcat (dry hole)	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Middle Cottlieb	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR 1125 National Bank of Commerce Bldg. San Antonio, Texas	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 700 feet from the North line and 1120 feet from the East line of Sec. 15-31N-14E San Juan Co., New Mexico	10. FIELD AND POOL, OR WILDCAT Wildcat
14. PERMIT NO. Approved 7-31-69	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 912 SL 6075.5 RD
12. COUNTY OR PARISH San Juan,	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☒ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On October 4, 1969 the above captioned well was plugged and abandoned as prescribed by the U.S.G.S. District Engineer and done in the following manner:

The entire borehole was circulated with heavy drilling mud from the top of the surface to the total depth of 9280 feet. The following cement plugs for formation protection were placed by Caliburton pump through drillpipe:

Plug Length	Interval	Cx. Cement.
100'	8725 to 8620	25
100'	7550 7450	25
100	4400 4300	25
100	3150 3050	25
100	1350 1250	25
50	400 350	18

10 cx. were placed in the top of the surface pipe and prescribed well marker installed. Arrangements for location restoration have been made.

18. I hereby certify that the foregoing is true and correct

SIGNED Ashton B. Green, Jr.
Geologist for: San Antonio, New MexicoTITLE Middle CottliebDATE Oct. 10, 1969

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

OCT 15 1969

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

Instructions

General: All forms designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or Federal procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for special instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.