

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
PO Box 289, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1140'S, 1720'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐
FRACTURE TREAT ☐ ☐
SHOOT OR ACIDIZE ☐ ☐
REPAIR WELL ☐ ☐
PULL OR ALTER CASING ☐ ☐
MULTIPLE COMPLETE ☐ ☐
CHANGE ZONES ☐ ☐
ABANDON* ☐ ☐
(other) ☐ ☐

To commingle Mesa Verde and Dakota formations

5. LEASE
NM 12014
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
EPNG B
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Blanco MV - Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28, T-32-N, R-6-W, NMPM
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6406' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

RECEIVED
NOV 15 1978
U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

To increase production from this well, it is planned to commingle the Mesa Verde and Dakota formations in the following manner:

Set bridge plug above Dakota perforations.
Run Gamma Ray Collar Correlation log and Cement Bond Log across Mesa Verde interval.
If necessary, perform remedial squeeze cementing.
Perforate and sandwater fracture the Mesa Verde formation.
Clean out and drill bridge plug and run tubing commingling the Mesa Verde and Dakota formations. NMOCC approval orders R-5794 and R-5795.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.


18. I hereby certify that the foregoing is true and correct

SIGNED H. G. Buices TITLE Drilling Clerk DATE November 13, 1978

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



OK