Form 9-331 (May 1963)

16.

UNITED STATES SUBMIT IN TRIPLICATE* DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side)

Form approved. Budget Bureau No. 42-Ry424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIME NAME

SF 079691

CEOL	OGICAL	SURVEY

			· •	
SUNDRY NOTICES	Λ NID	REPORTS	ON	WELLS
SOLING LACTICES	AITU	KEI OKIS	014	111665
e this form for proposals to	drill or to	deepen or plug	back to	o a different reservoir.

(Do not use this form for propos. Use "APPLICA	ils to drill or to deepen or plug back to a different reservoir. TION FOR PERMIT—" for such proposals.)		
OIL GAS X OTHER		7. UNIT AGREEMENT NA	
2. NAME OF OPERATOR El Paso Natural Gas Co	mpany	8. FARM OR LEASE NAM Gelbke	E
3. ADDRESS OF OPERATOR PO Box 990, Farmington	ı, NM 87401	9. WELL NO.	NOT DO AT
4. LOCATION OF WELL (Report location of See also space 17 below.) At surface	early and in accordance with any State requirements.* 1460'N, 960'W.	Blanco Pictured 11. SEC., T., R., M., OR B SURVEY OR AREA Sec. 11, T-31-	Cliffs Ext.
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH	13. STATE
	5955'GL	San Juan	New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	CE OF INTE	FULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*		WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other)
REPAIR WELL		CHANGE PLANS		(Otner) (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
(Other)			<u></u>	Completion or Recompletion Report and Log form.)

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *
 - TD 2770'. Ran 89 joints 2 7/8", 6.4#, JS production casing, 2759' set at 2770'. 12-24-72 Baffle set at 2759'. Cemented with 762 cu.ft. cement. WOC 18 hours. Top of cement at 1140'.
 - Tested casing to 4000#-OK. PBTD 2759'. Perf'd 2640-50', 2660-70', 2692-2702', 5-16-73 with 30 shots per zone. Frac'd with 30,000# 10/20 sand and 30,290 gallons water. Dropped 2 sets of 30 balls. Flushed with 655 gallons water.



MAY 2 3 1973

8. I hereby certify that the foregoing is true and correct SIGNED	TITLE Drilling Clerk	DATE May 23, 1973
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE