Form 9-331 (May 1963)

UNITED STATES BUBMIT IN TRIPLICATE* (Other instructions on reverse side)

	Form a Budget	Bures	u No.		
5. LEASE	DESIGN	ATION .	AND SI	TRIAL	No.

NM 0607

GEOLOGICAL SURVEY

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS
--------	---------	-----	---------	----	-------

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

4. LOCATION OF	990, Farmington, NM 87401 WELL (Report location clearly and in accordance with a ce 17 below.)	
See also spa At surface	1180'S, 1700'W	Blanco Pictured Cliffs Ex
	•	Sec. 35, T-31-N, R-10-
14. PERMIT NO.	15. ELEVATIONS (Show whether	NMPM 12. COUNTY OR PARISH 13. STATE
	6371'GL	San Juan New Mexi

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PULL OR ALTER CASING MULTIPLE COMPLETE SHOOT OR ACIDIZE REPAIR WELL CHANGE PLANS MATER SHUT-OFF WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other) WATER SHUT-OFF FRACTURE TREATMENT ALTERING WELL (Other) (Other) COMPLETE CHANGE PLANS (Other)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3259'. Ran 108 joints 2 7/8", 6.4#, J-55 production casing, 3249' set at 5-23-73 3259'. Baffle set at 3249'. Cemented with 481 cu.ft. cement, WOC 18 hours. Top of cement at 1680'.

PBTD 3249'. Tested casing to 4000#-OK. Perf'd 3157-72' and 3185-3200' 5-25-73 with 30 shots per zone. Frac'd with 30,000# 10/20 sand and 30,780 gallons treated water. Dropped one set of 30 balls. Flushed with 780 gallons water.



RECEIVED

		MAY 2 9 1973
VOIL (C)	· ·	U. G. GEOLOGICAL CURVEY
18. I hereby certify that the foregoing is true and correct SIGNED	TITLE Drilling Clerk	DATE May 29, 1973
(This space for Federal or State office use) APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE