NC. OF COPIES RECEIVED 5	
	Form Q-103
DISTRIBUTION	Supersedes Old C-102 and C-103
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE	
U.S.G.S. //	5a. Indicate Type of Lease
LAND OFFICE	State X Fee
OPERATOR I	5. State Oil & Gas Lease No.
	E 503-9
SUNDRY NOTICES AND REPORTS OF WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO ORILL OR TO DEEPEN OR PLUG BACK TO DIFFE ENT RESTRYOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.	
1	7. Unit Agreement Name
OIL GAS OTHER-	San Juan 32-7 Unit
WELL WELL OTHER-  2. Name of Operator	8. Farm or Lease Name
	San Juan 32-7 Unit
Northwest Pipeline Corporation 3. Address of Operator	9. Well No.
P.O. Box 90 Farmington, N.M. 87401	25
4. Location of Well	10. Field and Pool, or Wildcat
P 705 North 1680	Blanco Mesa Verde
UNIT LETTER B . 795 FEET FROM THE NORTH LINE AND 1680 FEET FROM	THITTHINITH THE
7U	MILLININI
THE East LINE, SECTION 36 TOWNSHIP 32N RANGE 7W NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	San Juan
6469' GR	
Check Appropriate Box To Indicate Nature of Notice, Report or Ot	her Data
NOTICE OF INTENTION TO: SUBSEQUEN'	T REPORT OF:
	<del></del> 1
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORABILY ABANDON COMMENCE DRILLING OPNS. XX	PLUG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB XX	
OTHER completion	
OTHER	
	in the of section and provinced
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	g estimated date of starting any proposed
work) SEE RULE 1903.	
8-1-74 Spud, drill $13-3/4$ " surface, run 5 joints $9-5/8$ " and set at	238' w/180 sacks.
Otroniano EO gooleg	
8-8-74 Ran 90 joints 7 20# J-55 & set at 3747' RKB w/176 Sacks 65/	35 Class "B" w/12% gel.
Followed w/50 facks class "B" w/2% cc.	
MOLLOWER WIDE FACKS CLASS D WIZE UV.	
Pollowed W/OU : acks class b w/2% cc.	
8-9-74 Drill cmt., blow hole dry.	
8-9-74 Drill cmt., blow hole dry.	
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2". 10.5#. J-55 Liner and set at 5923'	RKB. Liner hung at
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine	RKB. Liner hung at
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine	RKB. Liner hung at gilsonite/sack.
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/220 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z.	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal.	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/200 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799'	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal.	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/200 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799'	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/200 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799'	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/200 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799'	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/200 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799'	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran damma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/200 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799' 8-15-74 Shut in.	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Jamma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/200 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799'	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728',
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Camma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799' 8-15-74 Shut in.	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728', Fractured with 5000
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Camma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799' 8-15-74 Shut in.	RKB. Liner hung at gilsonite/sack. 8-5746', 5720'-5728', Fractured with 5000
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran damma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799' 8-15-74 Shut in.	RKB. Liner hung at gilsonite/sack.  8-5746', 5720'-5728', Fractured with 5000
8-9-74 Drill cmt., blow hole dry. 8-11-74 T.D. 5930' Ran Camma induction & gamma density. 8-12-74 Ran 72 joints of 4-1/2", 10.5#, J-55 Liner and set at 5923' 3601' RKB, w/2:0 sacks Class "B" w/4% gel & 1/2 cu.ft. fine Reversed out 75 sacks. 8-12-74 Spot 300 gal -1/2% HCL. Perf 5805-5824', 5756' - 5772', 573 5676'-5684', 5588'-5596', 5570'-5578', 7 zones with 16 s/z. gallon pad water & 80,000# 20/40 sand at 1#/gal. 8-14-74 Ran 186 Joints, 2-3/8", 4.6#, J-55 Tubing and set at 5799' 8-15-74 Shut in.	RKB. Liner hung at gilsonite/sack.  8-5746', 5720'-5728', Fractured with 5000

CONDITIONS OF A PROVAL, IF ANY: