

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved/
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

-00-2-1420-1709

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Lte. to. Lte

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Lte. to. Lte

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Llicat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14 - Twp. 31 - R. 10.

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water

2. NAME OF OPERATOR

Robert J. Anderson

3. ADDRESS OF OPERATOR

Lte. to. National Foundation, Inc.
355 S. 26th. St. Oklahoma City, Okla. 73112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.
At surface: 100 feet west of the south line and 600 feet
east of the east line of section 14 - Twp. 31 - R. 10.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5060 GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Log 1-2-75 to 8:00 p.m. and drilled a 2 7/8" surface hole
to approx. 520 feet.

2-4-75 ran 907 feet of 7" . . . 2-5-75 - 700' tri. surface casing
set at 614 feet (2 feet below ground level) and cemented by
alligator with 24 sacks of class "C" cement with 24 ball and
circulated to the surface.

A double-rod buffer flow-out-preventer was installed on the
surface casing and the surface casing was tested and held 600 psi.
before drilling out from under surface on 2-4-75 with a 6 1/2" hole.
Flow-out-preventer in use and frequently opened and closed to
test its operation to total depth.

Reported above to . . . by phone 2-7-75

18. I hereby certify that the foregoing is true and correct.

SIGNED

Ashton B. Teren

TITLE

Agent

DATE

March 10, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.