

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

076554

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hamilton-Federal

9. WELL NO.

2-A

10. FIELD AND POOL, OR WILDCAT

Blanco (Mesaverde)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 30, T32N-R10W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6104' K. B.

12. COUNTY OR PARISH

San Juan

13. STATE

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *


1. Perforation and treatment of the Mesaverde as follows:

(a) Perforated 5178'-88' (10 holes), 5195-97 (2 holes), 5198-5202 (8 holes), 5225'-30' (20 holes), 5258'-70' (20 holes), 5296-5300 (4 holes), 5304'-07' (6 holes), 5342'-52' (10 holes), frac above perms with 100,000 gal water and 72,000 lb sand.

(b) Perforated 5020-26 (7 holes), 5030'-34' (8 holes), 5046'-50' (7 holes), 5062'-66' (8 holes) and frac perms with 50,000 gal and 40,000 lb sand.

(c) Perforated 4600'-04' (4 holes), 4616'-20' (4 holes), 4756-60' (4 holes), 4774'-76' (2 holes), 4783' (1 hole), 4789' (1 hole), 4802'-10' (8 holes) & frac with 100,000 gal and 72,000 lb sand.

2. Cleaned out to T.D. and ran 2 3/8" tbg to 5352' K. B. with 4 1/2" production packer set @ 3025' K. B.



18. I hereby certify that the foregoing is true and correct

SIGNED

J. Elaker

TITLE

Prod. Engr.

DATE

5-13-75

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

