

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 010909

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Suter

9. WELL NO.

4A

10. FIELD AND POOL, OR WILDCAT

Blanco (Mesaverde)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 15, T32N-R11W

12. COUNTY OR PARISH

San Juan

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Mesa Petroleum Co.

3. ADDRESS OF OPERATOR

P.O. Box 2009 Amarillo, Texas 79105

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1640' FNL & 850' FWL Sec 15, T32N-R11W

San Juan County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6530' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) 7" Intermediate Casing

☐
☐
☐
☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

On 8/27/75 ran 7" Intermediate Casing as follows:

1.50 1 guide shoe

42.32 1 jt 7" casing with insert float in top

3471.01 87 jts 7" casing

Total of 3514.83 set at 3508' KBM. Cemented with 200 sacks HOWCO, 1/4#
flocelle/sack, and 50 sacks Class "B" 1/4# flocelle/sack 2% Calcium Chloride.

Plugged down at 2:15 PM 8/27/75.

Will run temperature survey after 8 hours.

RECEIVED

SEP 3 1975

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. L. Farrell

TITLE Operations Manager

DATE 8/28/75

(This space for Federal or State office use)


APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

XC:

TITLE
5 USGS (2 copies to state)
1 Archer

DATE



*See Instructions on Reverse Side