

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
Meridian Oil Inc.

3. Address & Phone No. of Operator
Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec, T, R, M.
1640'N, 1100'W Sec.3, T-31-N, R-10-W, NMPM

5. Lease Number
SF-078604

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Scott #13

9. API Well No.

10. Field and Pool
Undes. Pictured Cliffs

11. County and State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut Off

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

04-11-90 MOL&RU. Blow down. Killed well w/1% KCl wtr. ND WH. NU BOP. TIH w/DP, bit & scraper to 2700'. TOOH. TIH w/DP & 2 7/8" Baker RBP set @ 2648'. Load hole, PT csg 1500#, ok. TOOH w/DP. Ran GR-CCL & CBL 2648-1200'. (TOC 1380'.) Perf 2 holes @ 1365'. Pumped 16.5 bbls, no change. SDFN.

04-12-90 Pump 50 sx Class "G" w/D-60 FLA. Displaced down to 1325'. WOC.

04-13-90 Open BH, flow to blow tank. TIH, tag cmt @ 1295'. Circ cmt down to 1400'. TOOH. SD for weekend.

04-16-90 PT csg 700#, ok. TIH to 1450'. TOOH. Ran GR-CCL & CBL 1500-surface. Found cmt streamer from 788-832' w/100% bond. Perf'd 3 holes @ 788'. Squeezed w/100 sx Class "B" w/2% calcium chloride and 2# gilsonite, tailed w/175 sx Class "B" neat. TIH, circ cmt out, down to 738'. SDFN.

04-17-90 TIH, tag cmt @ 748'. Circ hole clean. Load hole & PT to 700#/15 min, ok. Ran GR-CCL & CBL surface - 900'. TOC @ 330'. Perf 3 holes @ 315'. Cmt w/140 sx Class "B" w/2% calcium chloride, circ 2 bbls cmt. WOC. SDFN.

04-18-90 TIHW/ DP, scraper & bit. Tag cmt @ 295'. Drl out squeeze & circ clean. TOOH. Load hole & PT to 700#. TIH, tag fill @ 2635'. TOOH. TIH w/DP & retrieving head. Circ sand off RBP. Latch onto plug & release. TOOH w/RBP. TIH, tag @ 2825'. TOOH LDDP. NDBOP. NUWH. Made 4 swab runs. Kicked around. Released rig.

14. I hereby certify that the foregoing is true and correct

Signed [Signature] Title Regulatory Affairs Date 4-19-90

ACCEPTED FOR RECORD

APR 23 1990

FARMINGTON RESOURCE AREA

BY [Signature]

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITION OF APPROVAL, IF ANY:

10000