

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

This form is not to be used for reporting packer leakage tests in Southeast New Mexico



NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operato Location	or	CONC	CO	INC		Lease		PR	TMO	Wc. No.		(PCM)
of Well:	UnitI	Sec06	Tw	P	31	Rgc.	1	0	Coı	antv S		
	NAME OF RESERVOIR OR POOL				TYPE OF PROD. (Oil or Gee)		METHOD OF PROD. (Flow or Art. LIII)		0.	PROD. MEDIUM (Tbg. or Ceg.)		
Upper Completion	PICTURED CLIFF				GAS		FLOW FLOW			TBG.		
Completion CHACRA MESA VERDE					GAS					TBG.		
	,			PRE-	FLOV	SHUT-IN	PRESSURE	DATA				
Upper Completion	1 VD = ID = 9 /			Length of time			SI press, psig	PC	161	Stabilized? (Yes or No)		
Lower Completion				Length of time	shut-in		Si press, paig	-CH- MV	156 — 161	Stabilized? (abilized? (Yes or No)	
						FLOW TEST	Г NO. 1			.	····	
Consmenced	at (hour, da	10)# 06-	19.	97				ucing (Up	per or Lower):	М.	LDDLE	
TIME LAPSED TIME			Up	PRESSURE Upper Completion Lo		.ower Completion	PROD. Z		REMARKS			
86- <u>1</u> 7-	<u>-97</u>	1-DAY	14	PC M	V	CH 135		•	вотн 2			ΓN
06-18-	-97	2-DAYS	15	0 16	1	145			вотн 2		*************************************	
06-19-	-97	3-DAYS	1.6	1 16	1	156			вотн г			
06-20-	-97	1-DAY	<u>.11</u>	9 16	1	79			MIDDLE	ZONE	FLOWI	NG
06-21-	-97 ·	2-DAYS	11	9 16	1	84			MIDDLE	ZONE	FLOWI	NG
roduction		uring test BOPD	bas			Bbls. ir				zav	GOR	
· · · · · · · · · · · · · · · · · · ·						SHUT-IN PI	RESSURE D	ATA				
Upper empletion	. 3			ength of time st	· – -	SI press. psig	press, psig			Stabilized? (Yes or No)		
Lower moletion			L	ength of time sh		SI press, paig	I press, paig			Stabilized? (Yes or No)		

FLOW TEST NO. 2

TIME (hour, date)			Zone producing (Upper or Lower):				
· · · · -	LAPSED TIME	PRES	RUME	PROD. ZONE	REMARKS		
	SINCE **	Upper Completion	Lower Completion	TEMP.			
		1					
s:	BOF		PD: Tested thru	(Orifice or Meter):	Grav GOI		
proved		0 1997	19 C	mplete to the best of	С		
	•	^	В	by	DINY S		
	Johnnyl	Rollinson & Gas Inspector			Col. Prod. Sup 7-22-97		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture rreatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shur-in while the zone which was previously shur-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).