## UNITED STATES DEPARTMENT OF THE INTERIOR SUBMIT IN TRIPLICATE\* (Other instructions on reverse side) GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or ping back to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals.)

WELL DOTHER Dakota test (Dryhole)

5929 N. May Ave. Oklahoma City, Oklahoma 73112
L. DOLATION OF WELL (Report location clearly and in accordance with any State requirements,\*
See also space 17 holow.) 1850 FSL - 1850 FEL

Sec.15 - T31N - R16W

5704 GR

Robert C. Anderson 8. ADDRESS OF OPERATOR The Summit Bldg. - Suite 411

5. LEASE DESIGNATION AND SERIAL NO.

## M-00-C-1420-1710

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute	Mtn.	Ute

Budget Bureau No. 42 R1424.

-	7. UNIT AGREEMENT NAME
	None
	None 8. Faith of Lease name
	Ute MtnAGA
	9. WELL NO.

10, FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR BLR. AND SEC. 15 - T31N - R16W N.M.P.M.

12. COUNTY OR PARISH 13. STATE San Juan

Straight Canyon Dakot

14 PERMIT NO.

2. NAME OF OPERATOR

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

5715 KB

1 15. ECEVATIONS (Show whether DF, RT, GR, etc.)

NOTICE OF INTENTION TO:				SCHNEQUENT CEPOUL OF.		
r	r	,	-			
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT		MULTIPLE COMPLETS		FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE		AHANDON*	X	SHOOTING OR ACIDIZING	ABANDON MENT*	
GEPAIR WELL		CHANGE PLANS		(i)ther) (NOTE: Report results of multiplication or Recompletion Recom	tiple compistion on Well eport and Log form.)	l

17 to scattle processed on completed of practions (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work. nent to this work.)\* The above captioned well has been tested and found to indicate non-commercial productivity; therefore, it is proposed that the well be abandoned in the following manner and according to previously received instructions as follows:

> 22001. 1). Cement plug T.D. to

2). Cut & pull 4%" Csg. and place a 100' cement plug (50' inside 4½" & 50' on top of csg. cut ).

3). 100' cement plug 1700' to 1600' over top of Gallup.
4). 100' cement plug 560' to 460' across 8 5/8" shoe.

50' cement plug 50' to surface with Marker.

Surface area will be cleaned and re-habilitated as prescribed.

It is proposed that this work commence at the earliest rigariabilit

SIGNED Ashton B. Geren, Jr.

TITLE Agent for: Robert C. Anderson

DATE August 3, 1980

This space for Federal or State office use)

CONDITIONS OF APPROVAL, IF

ah 3 ml

AUG 1 1 1980

CARL A. BARRICK MO-DISTRICT ENGINEER \*See Instructions on Reverse Side

NMOCD