

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42 B4424.

5. LEASE DESIGNATION AND SERIAL NO.

NM01594

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Kelly A

9. WELL NO.

3A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., M., OR B.L.K. AND
SURVEY OR AREA

Sec. 15, T-31-N, R-10-W
N.M.P.M.

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

El Paso Natural Gas Company

3. ADDRESS OF OPERATOR

Box 990, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1750'S, 1650'E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6218' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

08-21-76 T.D. 3351'. Ran 85 joints 7", 20#, KS intermediate casing, 3339' set at 3351'. Cemented with 455 cu. ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement at 2975'.

08-16-76 T.D. 5636'. Ran 76 joints 4 1/2", 10.5#, KS casing liner, 2442' set 3194-5636'. Float collar set at 5619'. Cemented with 424 cu. ft. cement WOC 18 hours.

10-30-76 PBTD 5619'. Tested casing to 3500#, O.K. Perfed 4599', 4643', 4677', 4734', 4736', 4745', 4748', 4750', 4757', 4768', 4794', 4799', 4813', 4817', 4838', 4844', 4858', 4863', 4960', 4966' with 1 shot per zone. Fraced with 30,000# --20/40 sand and 29,988 gallons water. No ball sets dropped. Flushed with 6468 gallons water. Perfed 5064', 5082', 5085', 5160', 5171', 5198', 5224', 5226', 5237', 5254', 5258', 5273', 5277', 5281', 5325', 5327', 5356', 5366', 5480', 5536' with 1 shot per zone. Fraced with 52,000# --20/40 sand and 51,996 gallons water. No ball sets dropped. Flushed with 6804 gallons water.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. G. Bues

TITLE

Drilling Clerk

DATE

NOV 8 1976
November 8, 1976

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side