| Form 9-331 (May 1963) | DEPARTM | INITED STATES TENT OF THE INTER EOLOGICAL SURVEY | SUBMIT IN TRIPLICATE* (Other instructions on re- verse side) | Form approved, No. 42 R1424. 5. LEASE DESIGNATION OF SECTIAL NO. UTC Mtn Fribal MXO-C-1420-0625. 6. If INDIAN, ALIGHTEE GOVERNME NAME |
|--|---|---|---|--|
| (Do net | SUNDRY NOTE | ON WELLS to a different reservoir, proposals.) | Ute Mountain Tribal | |
| OFL WELL | GAS VELL V OTHER | | | 7. UNIT AGREEMENT NAME |
| 2. NAME OF OPE | RATOR | 8. FARM OR LEASE NAME | | |
| El Paso N | Catural Gas Comp | Pinon Mesa D | | |
| P. O. BOX 4. LOCATION OF See also spac At surface | c 990 Farmingte wer. (Report location close 17 below.) | 2 10. FIELD AND POOL, OR WILDCAT Basin Dakota | | |
| 800'S, 60 | 00 'E | 11. SEC., T., R., M., OF BEZ. AND SURVEY OF AREA Sec. 13, T-31-N, R-14-W | | |
| 14. PERMIT NO. | | 15. ELEVATIONS (Show whether | DF, RT, GR, etc.) | N.M.D.M. 12 COUNTY OF PARISH! 12. STATE |
| | | 5681' GL | | San Juan New Mexico |
| 16. | Check Ap | propriate Box To Indicate | Nature of Notice, Report, or C | |
| | NOTICE OF INTENT | subsequ | JENT REPORT OF; | |
| proposed v nent to thi | CODIZE A L COMPLETED OFFR Work. If well is direction s work.)* TD 6504'. Ran 6504'. Float | nally drilled, give subsurface loo 1 155 joints 4 1/2" Collar set at 6488 | Completion or Recomplent details, and give pertinent dates, | 4424' and 1754'. |
| 03-22-76 | cement; third surface. PBTD 6488'. T 6327', 6344', | Stage with 673 cu. Tested casing to 40 6365', 6378', 6388 gallons treated was | ft. cement. WOC 18 h CO#OK. Perf'd 6230' ' with 7 holes. Frac' ater. Dropped no sets | ours. Top of cement at , 6240', 6276', 6308', d with 60,000#40/60 |
| | | | RECEIVED MAR 3 0 1976 OIL CON' | |

| 18. I hereby certify that the foregoing is true and cor | rect | |
|---|----------------|--------------|
| SIGNED M. M. Dricco | Drilling Clerk | DATE 3-23-76 |
| (This space for Federal or State office use) | | |
| APPROVED BY | TITLE | DATE |
| CONDITIONS OF APPROVAL, IF ANY: | | MAR 2.5 1976 |

*See Instructions on Reverse Side

