Form 9-331 (Mny 1983)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on re-

SUBMIT IN TRIPLICATE.

Budget Burenn No. 42 R1424 SCHLAMM DUMINATION AND BERTAL NO.

GEOLOGICAL SURVEY	SF 078604
SUNDRY NOTICES AND REPORTS (Do not use this form for proposals to drill or to deepen or plug Use "APPLICATION FOR PERMIT" for such in	back to a different reservoir.
I. OIL GAN WELL A OTHER	7. UNIT AGICEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
El Paso Natural Gas Company	Scott
3. ADDRESS OF OPERATOR	9. WELL NO.
P. O. Box 990, Farmington, New Mexico 87. LOCATION OF WELL (Report location clearly and in accordance with any See also space 17 below.)	y State requirements.
At surface	, Undes. Pictured Cliffs
1625' N, 1185' W	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Sec. 29, T-32-N, R-10-NMPM
14. PERMIT NO. 15. ELEVATIONS (Show whether D	of, RT, GR, etc.) 12. COUNTY OR PARISH 13. STATE
6021' GL	San Juan New Mexic
16. Check Appropriate Box To Indicate	Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING	WATER SHUT-OFF X REPAIRING WELL X ALTERING CASING
FRACTURE TREAT MULTIPLE COMPLETE	PRACTICAL TRUSTANIA
SHOOT OR ACIDIZE ABANDON*	SHOOTING OR ACIDIZING ABANDONMENT*
REPAIR WELL CHANGE PLANS	(Other) (Note: Report results of multiple completion on Well
(Other)	Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OF COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

T.D. 2982'. Ran 94 joints 2 7/8", 6.5#, J-55 production casing, 2972' set at 2982'. Baffle set at 2972'. Cemented with 832 cu. ft. cement. 11-21-76 WOC 18 hours. Top of cement at 650'.

Tested casing to 4000#-ok. 12-15-76 PBTD 2972'. Perf'd 2845', 2847', 2856', 2859', 2868', 2871', 2881', 2883' with 1 shot per zone. Frac'd with 35,000#--10/20 sand and 35,410 gallons treated water. Dropped no sets of balls. Flushed with 715 gallons water.

DEC 1 / 1976

SIGNED SIGNED	TITLE Drilling Clerk	DATE December 16, 1976
(This space for Federal or State office use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE