

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well ☒ other ☐
-
2. NAME OF OPERATOR
El Paso Natural Gas Company
-
3. ADDRESS OF OPERATOR
PO Box 289, Farmington, NM 87401
-
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1100'N, 1520'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
-
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
SF 078604
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Scott
9. WELL NO.
18
10. FIELD OR WILDCAT NAME
Mt. Nebo Fruitland
11. SEC., T., R., M., OR BLK. AND SURVEY OR
AREA
Sec. 34, T. 32-N, R. 10-W, NMPM
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6187' GL

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input checked="" type="checkbox"/>
(other)	

□ □ □ □ □ □ □ □

REC'D

2000

U. S. DEPARTMENT OF COMMERCE
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Since it was determined this well has a casing failure, it is intended to plug and abandon this wellbore in the following manner:

Tag cement inside casing at 1519'. Spot 7 sk. plug inside casing across Ojo Alamo from 1275' to 1519'.

Cut off 2 7/8" casing at approximately 1100'. Spot 30 sec plug on top of casing stub. Recover 1100' of 2 7/8" casing.

Spot a 30 sk. plug from 86' to 186' to isolate surface casing shoe. Set dry hole marker at surface, with 15' surface plug.

Verbal approval was received from Mr. Beecher on April 8, 1982 to perform

Subsurface Safety Valve: Manu. and Type this work. Set @ 300 Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED [Signature] TITLE Drilling Engineer DATE April 13, 1982

APPROVED _____ (Leave space for Federal or State office use)

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY: APR 19 1962

For JAMES F. SIMS
DISTRICT ENGINEER

NMOCC