

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1500'N, 1730'W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 080917

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Atlantic B

9. WELL NO.  
6A

10. FIELD OR WILDCAT NAME  
Blanco M.V

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
33, T-31-N, R-10-W  
N.M.P.M.

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6167' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-26-79: PBTD 5537'. Tested casing to 4000#, Ok. Perfed Mass. & P.L. 5107, 5114, 5126, 5131, 5136, 5140, 5156, 5162, 5168, 5173, 5180, 5189, 5196, 5216, 5238, 5254, 5308, 5357, 5390, 5455, 5468'. w/1 SPZ. Fraced w/74,500# 20/40 sand and 149,000 gal. water. Flushed w/6888 gal. water. Perfed C.H. & Men. 4381, 4500, 4512, 4531, 4551, 4598, 4614, 4620, 4626, 4637, 4643, 4679, 4685, 4774, 4847, 4878, 4938, 4947, 4980, 4990, 5032'. w/1 SPZ. Fraced w/78,000# sand and 156,000 gal. water. Flushed w/6594 gal. water. Perfed P.C. 2860-2908' w/1 SPZ. Fraced w/48,000# 10/20 sand and 55,980 gal. water. Flushed w/4914 gal. water

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct


SIGNED D. G. Drisco TITLE Drilling Clerk DATE July 5, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side



James L. [Signature]