

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)


1. oil well <input type="checkbox"/> gas well <input checked="" type="checkbox"/> other	
2. NAME OF OPERATOR ENERGETICS, INC.	
3. ADDRESS OF OPERATOR 102 Inverness Terrace East, Englewood, Colorado 80112	
4. LOCATION OF WELL (REPORT LOCAT ON CLEARLY. See space 17 below.) AT SURFACE: 890'/S, 2000'/W AT TOP PROD. INTERVAL: same AT TOTAL DEPTH: same	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
5. LEASE MPO-C-1420-1717	6. IF INDIAN, ALLOTTEE OR TRIBE NAME MOUNTAIN UTE
7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME UTE 11
9. WELL NO. 24	10. FIELD OR WILDCAT NAME VERDE GALLUP
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA 11-31N-15W	
12. COUNTY OR PARISH SAN JUAN	13. STATE NEW MEXICO
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB AND WD) 5790 GL	

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in rotary tools and spudded 12 1/4" hole on 03/16/79. Drilled to 96' and ran 8 5/8" 24# casing to 93'. Cemented with 70 sk. class "B" with 2% CaCl<sub>2</sub>. Circulated 10 sk. cement. Plug down at 2330 hours, 03/16/79.



Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John Alexander TITLE AGENT DATE June 20, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: