UNITED STATES DEPARTMENT OF THE INTERIOR

UNITED STATES	f				/
UNITED STATES	5. LEASE		Š	3 30 € 2 × 50	
DEPARTMENT OF THE INTERIOR	SF 0783	16E 5	***	6 8 8 2 2 3 4	
GEOLOGICAL SURVEY	6. IF INDIAN,	ALLOTTEE	OR TR	IBE NAME	
		8		क्रांतिज्ञ	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGR		AME -	1. E	
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)		<u> </u>		<u> 777</u>	
eservoir, Use Form 9-331-C for such proposals.)	8. FARM OR		IE .	2.57 t	
1. oil gas X other	<u>Walker</u>		+:		
Well Street	9. WELL NO.	g. 60 m.	<u></u>		
2. NAME OF OPERATOR	4	- # & O	34	<u> </u>	
El Paso Natural Gas Company	10. FIELD OR			eca iii	
3. ADDRESS OF OPERATOR	Blanco				
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., F	к., м., ок в с.:: 32,5 °			
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	711127 36			I	••
AT SURFACE: 1450'S, 1450'E	12. COUNTY O				_
AT TOP PROD. INTERVAL:	San Jua			w Mexic	:0
AT TOTAL DEPTH:	14. API NO.			og fr	
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			£1.	중취원님	
REPORT, OR OTHER DATA	15. ELEVATIO	NS (SHOW	DF, K	DB, AND	WD)
	6322' G		À	1,55	- •
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		\$ £ 8 8	(%	10 6 9 Q	
TEST WATER SHUT-OFF U X			:- :-	9.8 2.4	
SHOOT OR ACIDIZE			ij		
REPAIR WELL	(NOTE: Report	results of mi	titiple co	ompletion or	zone
PULL OR ALTER CASING		on Form 9-		2 % T I	
MULTIPLE COMPLETE CHANGE ZONES	-	2282	<u> </u>		ĝ.
CHANGE ZONES	- 2		Ē.		
other)	<u>.</u>		==	B C Z E	ausilaman
		<u> </u>	====	- 12 B 10 B	
 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statingly including estimated date of starting any proposed work. If well is described.) 	te all pertinent d	letails, and	give p	ertinent da	ates, and
measured and true vertical depths for all markers and zones pertiner	nt to this work.)*	ار در اور اور اور اور اور اور اور اور اور او	ارگر ارگر		unu
		공유되었다.	<u>.</u>	82/3	
5-2-79: Spudded well. Drilled surface hole.	Ran 5 jts	8 5/8	", 24	4# ,∈ J-5!	5
surface casing, 204' set at 216'. C	Cemented w/1	65 cu.	ft. (cement.	
Circulated to surface. WOC 12 hours	s; held 600#	/30 min	utes	• <u>2</u> 2 2 2 2	
		是	į.		
		in, ap. 2.			
			90	* 5 1 5	
			É	3 B 25	e 187
		ರತ್ತ * . *	- Te /		14
		tracilles.	enoitourueni enoitourueni		1
		of Table	3.4	6 2 2	APP TO THE STATE OF
			3 E 5 5 5 5 5 5 5 5 5		" pak " " " " " " " " " " " " " " " " " " "
•		直見り	2.5	E STEEL	
Subsurface Safety Valve: Manu. and Type		= a < Set	side oriquis	1 0	ຼັ Ft. ້ ຸ
		100 mm 10		10 to 00 to	
18. I hereby certify that the foregoing is true and correct		Secondary May	es	20 mm, 15	
SIGNED W. D. Dusco TITLE Drilling Cle	erk date	May 3,	197	96 8 3 B	
	fice use)	<u> </u>		<u>- 6 6 6 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 </u>	
(This space for Federal or State of	nce use)	to to the control of	15 H	9444 S	
APPROVED BY TITLE	DATE _	三面 三二	den	3. 71	
CONDITIONS OF APPROVAL, IF ANY:		med redibbe ni etnos biult guíq evede eneriones	or Es	General Indications Indications Indications	
		A COLOR	0 93	3 H 2 S	
			etstê	Gibal Fuga Goog	