

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
720 S. Colorado Blvd., Denver, CO 80222
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 860'FNL, 790'FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Status Report: casing

SUBSEQUENT REPORT ON

RECEIVED
JAN 17 1980
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

5. LEASE
USA-SF-078095
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Case A
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Dakota 11
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 19; T31N; R11W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6056'GL

NOTE: Report results of multiple completion or zone change on Form 9-330.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/29-11/10/79

Spud 13 3/4" hole 10/29/79. Ran and set 5 jts 9 5/8", K55, 36#csq @ 217'. Cmt w/200 sxs regular w/2% CACL2. Circ. to surface. Reduced hole to 8 3/4" and drilled to 3497', on 11/5 ran and set 78 jts of 7", 23#csq. Cmt. w/525 sxs Howco lite followed by 150 sxs CL B w/2% CACL2. Circ. to surface. Reduced hole to 6 1/4" and resumed drilling. On 11/10 ran 118 jts of 4 1/2" csq w/liner and set at 7265'. TOL: 3318'. Cmt. w/525 sxs 150/50 Pozmix and 4% gel. Reversed out cmt. PD. Released rig 11/10/79. WOCU.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Carley Thornton TITLE Admin. Supervisor DATE 1/14/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NMOCO