

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
890'S, 1760'W  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other)

SUBSEQUENT REPORT OF:

☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 081155

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
Allison Unit

8. FARM OR LEASE NAME  
Allison Unit

9. WELL NO.  
52

10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 28, T-32-N, R-6-W  
NMPM


12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6702' GL

(NOTE: Report results of multiple completion or zone change on Form 9-331.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-8-81: PBTD 6404'. Tested casing to 3500#, OK. Perfed Massive P.L.: 5968, 5972, 5984, 5987, 5990, 5994, 5997, 6020, 6027, 6032, 6038, 6048, 6055, 6061, 6088, 6151, 6159, 6207, 6239, 6256, 6317, 6339, 6401, 6405' W/1 SPZ. Fraced w/ 64,500# 20/40 sand, 116,000 gal. wtr. Flushed w/ 2600 gal. wtr.

5-10-81: Perfed Cliff House & Menefee: 5667, 5698, 5710, 5758, 5762, 5787, 5791, 5821, 5826, 5838' W/1 SPZ. Fraced w/ 23,000# 20/40 sand, 33,000 gal. wtr. Flushed w/ 7520 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Susac TITLE Drilling Clerk DATE May 13, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMOC