Form	9-331
(May	1963)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other Instructions on reverse side) GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATES

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR

WE'L X

SOLAR PETROLEUM, INC.

GAS WELL

S. FARM OR LEASE NAME Navajo 'F'

3. ADDRESS OF OPERATOR

One Denver Place, Suite 1300,

9. WELL NO. 153 CO 80202

10. FIELD AND POOL, OR WILDCAT

LOCATION OF WELL (Report location clearly and in accordance See also space 17 below.)
At surface

with any State requirements MAY 89 Bol

199 tath Stis Denver

Horseshoe Gallup 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

1330' FSL, 1330' FWL

D. S. GEOLDGHCAL SURVEY FARMINGION, N. M.

10-T31N-R17W

14. PERMIT NO.

15. ELEVATIONS (Show whether or, ar, or, etc.

12. COUNTY OR PARISH | 13. STATE

SUBSEQUENT REPORT OF:

5213' GR

New Mexico San Juan

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO: TEST WATER SHUT-OFF

PULL OR ALTER CASING MULTIPLE COMPLETE

WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING REPAIRING WELL ALTERING CASING ABANDONMENT⁴

FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

CHANGE PLANS

ABANDON*

(Other) Spud & Casing Record (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

(Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Date Spudded: 2-10-81 Date TD Reached: 2-23-81 Date Completed: 3-18-81

Total Depth: 940'

CASING RECORD:

Set 8-5/8", 24#, at 91.74' (hole size: $12-\frac{1}{4}$ "). Cemented with 100 sx Class 'B', 1#/sx flake, 3% cc.

Set $4-\frac{1}{2}$ ", 10.5#, at 927' (hole size: $6-\frac{1}{2}$ "). Cemented with 300 sx 50-50 POZ, 2% gel, 10% salt, .5 of 1% Halad 4.

2-3/8" TUBING set at 887'.

18. I hereby certify that the foregoing is true and correct		
SIGNED	TITLE Senior Petroleum Engineer	DATE May 26, 1981
(This space for Federal or State office use) APPROVED BY	TITLE	DATE