

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐  
2. NAME OF OPERATOR  
El Paso Natural Gas Company  
3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, NM 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1120'N, 1520'W  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒ RECEIVED  
SEP 18 1981  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
SF 078389- A  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
San Juan 32-9 Unit  
8. FARM OR LEASE NAME  
San Juan 32-9 Unit  
9. WELL NO.  
45A  
10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 12, T-31-N, R-10-W  
NMPM  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6277' GL



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

-9-81: PBDT 5806'. Tested casing to 3500#, Held Ok. Perfed Point Lookout:  
5360, 5390, 5395, 5400, 5416, 5429, 5434, 5447, 5452, 5470, 5487, 5510, 5621, 5628, 5662,  
5678, 5714' W/1 SPZ. Fraced w/ 60,000# 20/40 sand, 120,000 gal. wtr. Flushed  
w/ 7014 gal. wtr.

Perfed Cliff House & Menefee:

4662, 4710, 4805, 4856, 4904, 4964, 4982, 5003, 5016, 5027, 5036, 5131, 5136, 5247, 5300' W/1  
SPZ. Fraced 57,500# 20/40 sand, 115,000 gal. wtr. Flushed w/ 6552 gal. wtr.

-10-81: Set Bridge Plug at 4000. Pressure tested held ok. Shot 1 squeeze hole at 1625'.  
Set Full bore packer at 1465'. Cemented w/118 cf. cmt.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED M. P. Duce TITLE Drilling Clerk DATE September 17, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC

BY FARMINGTON DIST. 3  
17/81