

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR
Tenneco Oil Company

3. ADDRESS OF OPERATOR
P. O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 420' FNL 1660' FWL "C"
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Squeeze details

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
SF-078040

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Childers

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Basin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 1, T31N R11W

12. COUNTY OR PARISH 13. STATE
San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6328' gr.

(NOTE: Report results of multiple completion zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/26/81 - Squeezed DV tool w/150 sx Class B w/1% CaCl_2 and 6-1/4# Gilsonite. Reversed circulation through pkr. Reset pkr and pressured up to 3500 PSI. Closed valve.

4/28/81 - Released pkr and POOH w/tbg and pkr. RIH w/tbg and 6-1/4" bit. Tagged cmt @ 2977'. Drill out cmt. Pressure test DV tool to 3500 PSI. Test good. POOH w/tbg and bit. RIH w/tbg and retrieving head for bridge plug. Tag top of BP. Circ hole clean w/1% KCL water. Released BP. POOH w/BP and tbg and 4-1/2" fullbore pkr to top of liner.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Curly Statten TITLE Asst.Div.Adm.Mgr. DATE 5/5/81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

NMOC

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 12 1981

FARMINGTON DISTRICT