

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR  
SUPRON ENERGY CORPORATION
3. ADDRESS OF OPERATOR  
P.O. Box 808, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 800 ft./N ; 1080 ft./W line  
AT TOP PROD. INTERVAL: Same as above  
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒ RECEIVED  
JUL 14 1981  
(NOTE: Report results of multiple completion or zone change on Form 9-330.)  
☐ U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
SF 078464
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Federal "A"
9. WELL NO.  
1-E
10. FIELD OR WILDCAT NAME  
Blanco Mesaverde; Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 25, T-31N, R-13W, NMPM
12. COUNTY OR PARISH 13. STATE  
San Juan New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5799 R.K.B.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Spudded 12 $\frac{1}{4}$ " surface hole at 5:00 p.m. 7-11-81.
2. Drilled 12 $\frac{1}{4}$ " surface hole to total depth of 286 ft. R.K.B.
3. Ran 6 joints of 8-5/8", 24.00#, H-40 casing and set at 286 ft. R.K.B.
4. Cemented with 200 sacks of class "B" with 3% calcium chloride. Plug down at 12:00 midnight 7-11-81. Cement circulated to surface.
5. Waited on cement for 12 hours.
6. Pressure-tested casing to 800 P.S.I. for 30 minutes. Held OK.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Roddy TITLE Production Supt. DATE July 13, 1981  
Kenneth E. Roddy

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 17 1981

\*See Instructions on Reverse Side

NMOCG

BY Dean Elliott  
FARMINGTON DISTRICT