

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other ☐
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
P. O. Box 3249 Englewood, CO 80155
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 900' FNL, 920' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



5. LEASE
SF-0780501-0.78051
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Neal Com.
9. WELL NO.
1E
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 15, T31N, R11W
12. COUNTY OR PARISH
San Juan
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5934' gr.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/21/82--MIRURT. Spud well 1/21/82. RU & run 7 jts 9 5/8" 36# K-55 ST&C csg. Land @ 285'.
Cmt w/280 sx CL-B + 2% CALC₂ + 1/4#/sx celoflake. Circ 2 bbls excess cmt. NUBOP.
1/28/82--TD into hole 1:30 a.m.
1/29/82--SLM REV to 4772'. RU & run 114 jts 7" 23# K-55 STC csg. Set @ 4772'. DV @ 2868'.
Circ csg. cmt w/94 sx Lo-dense. Tail w/150 sx CL-B. Lost circ w/96 bbl displ.
Cmt 2nd stage w/160 sx Lo-dense 1/4# sx Flocele. Tail w/150 sx CL-B + 1/4#
sx Flocele. Good circ. No cmt to surface. NUBOP. Temp survey shows TOC 1150'.
Drill DV. Drill cmt to unload.
1/30/82--Circ hole clean w/NOWSOO to unload.
2/1/82-- Trip to LD SQ DC.
2/2/82-- TD well on 2/1/82.
2/3/82-- RU & run 8 jts 4 1/2" 11.6# K-55 ST&C & 54 jts 10.5 K-55 ST&C. TIH w/liner.
(over)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Sandra Peron TITLE Production Analyst DATE 2-8-82

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC

ACCEPTED FOR RECORD

FEB 24 1982

FARMINGTON DISTRICT

BY 293

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

2/3/82 (cont)--Set @ 7265' w/LC @ 7217', TOL @ 4601'. Blow
hole. CMT w/135 sx CL-B + additives. Tail w/150 sx
CL-B neat. Reverse out 5 bbls CW-100. LDDP, NDBOP,
rig released.