API#

30-045-25337

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## **OIL CONSERVATION DIVISION**

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

_	BURLING	GTON I	RESOURC	ES OIL & G	GAS CO.		Lease	CALLOWAY		· · · · · · · · · · · · · · · · · · ·	Well No.	3
Location of Well:	Unit	E	Sect	22	Twp.	031N	Rge.	011W	County	SAN JUAN		
	-				IR OR POO			YPE OF PROD.	<u> </u>	OD OF PROD.	PRO	OD. MEDIUM
								(Oil or Gas)	(Flo	w or Art. Lift)	(	Гbg. or Csg.)
Upper Completion	PICT	rured	CLIFFS					Gas Flow		Flow	Tubing	
Lower Completion	DAK	ОТА						Gas		Flow	ow Tubing	
	•				PRE-I	LOW SHUT-IN	PRESS	URE DATA	1		•	
Upper	Hour	, date sh	ut-in	Length of time shut-in			SI press. psig			Stabilized? (Yes or No)		
Completion	4/18/98			120 Hours			438					
Lower Completion	4/18/98				72 Hours			702				
						FLOW TES	ST NO.					
	l at (hour,date)*			4/21/98				Zone producing ( PROD. ZONE	Upper or Lower) LOWER			
TIME	LAPSED TIME			PRESSU				DELLARIA				
(hour,date)	SINCE*		Upper C	Upper Completion Lower Co		letion TEMP			REMARKS			
4/22/98	96 Hours		443		238				Turned lower zone on			
4/23/98	120 Hours			443		244				NEGEIVED		
									OUL COUR DUN		1988	
		<del> </del>								DUS		DUN
Production rate	2 40000				<del>.</del>	-						
r rounction rate	e uui mg	ıcsı										
Oil:		BOPD	based on		Bbls. ii	n	Hours	<u> </u>	Grav		_ GOR	
Gas:				MCFPD;	Tested thru (	Orifice or Meter):	: _	· · · · · · · · · · · · · · · · · · ·				
					MID-	TEST SHUT-IN	PRESS	URE DATA				
Upper Completion	Hour, date shut-in			Length of time shut-in			SI press. psig			Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in			Length of time shut-in			SI press. psig			Stabilized? (Y	es or No)	·

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (Root, Ba	110/ + +		Zone producing (Upper	er Lower):	
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE	
(hour, date)	SINCE * *	Upper Completion	Lower Completion	TEMP.	REMARKS
		<del></del>		<del> </del>	
		<del> </del>	<del></del>	<del> </del>	
:		1			
	<del></del>	<del> </del>		<del> </del>	
			[		
<del></del>	<del>                                     </del>				
			1		
<u> </u>	. L		1	· · · · · · · · · · · · · · · · · · ·	
Production rate d	luring test				
	· ·				
Oil:	ВОР	D based on	Bbls, in	. Hours	Grav GOR
Gas:		МСР	PD: Tested thru	(Orifice or Meter):	······································
		·· <del>·</del>		(,	
Remarks:		And the second of the second o	and the state of t		
:			<u>-</u>		
I hereby certify th	hat the informati	on herein contain	ed is true and co	mplete to the best	of my knowledge
Approved	UIN 22	1976	. 19	Derator SW	ington Lesonsces
New Mexico O	il Conservation E	Division		// /	
:			F	· Polace	m associate
·	0	1		-	. 6
Ву	change (X)	en-naroun	т	ida Pollar	in moesate
				inc - Contact	in some and
Title	Jeputy Oil & G	as inspector	r	Date	7/98
			<del></del>	- E/1.	1.0
				,	

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shur-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).