

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (505) 334-8478 FAX: (505) 334-6170

http://emnsd.state.nm.us/ocd/District III/3distric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

> Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

	NAME OF RESE	RVOIR OR POOL	TYPE O	F PROD.	METHOD OF PROD.	PROD MEDIUM
	NAME OF RESERVOIR OR POOL			r Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)
Upper Completion	Pictured Cliffs		gas		flowing	tubing
Lower Completion	Mesaverde	gas		flowing	tubing	
		PRE-F	LOW SHUT-II	N PRESSURI	E DATA	
Upper Completion	Hour, date shut-in 10-25-00		Length of time s	shut-in days	SI press. Psig	Stabilized? (Yes or No)
Lower Completion	Hour, date shut-in 10-25-00		Length of time s	shut-in days	St press. Psig 322	Stabilized? (Yes or No) yes
			FLOW TE	ST NO. 1		
Commenced at ((hour, date)*		•	Zone producing	(Upper or Lower):	
TIME (hour,date)	LAPSED TIME SINCE	Upper Completion I	JRE	PROD. ZONE TEMP.		REMARKS
10/29/00	24 hrs	143	301		Flowed PC. MV	SI, PC pressure hig
10/30/00	48 hrs	140	295			SI, PC pressure hig
			EAU mm			
		,	FAILED			
			:			
	ł i					
Production ra	ate during test					
	ate during test	BOPD based	i on	Bbls. in_	Hours	_GravGOR
Oil:	ate during test		i on PD; Tested th			_GravGOR
Oil:	ate during test	MCF		ru (Orifice or	Meter):	_GravGOR
Production ra Oil: Gas: Upper Completion	ate during test Hour, date shut-in	MCF	PD; Tested th	ru (Orifice or I PRESSURE	Meter):	GravGOR

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):		
TIME (hour,date)	LAPSED TIME Since**		Lower Completion	PROD. ZONE	REMARKS	
	•,					
					· · · · · · · · · · · · · · · · · · ·	
-						
					<u> </u>	
	te during test	. has a l				
vil: as:	BOPD		Bb FPD:Tested thru		ursGravGOR	
emarks:	BOPD					
oil:emarks: nereby certif	BOPD y that the inform	nation herein cor	ntained is true an	nd complete to the	bes of my knowledge.	
oil:emarks: nereby certif	BOPD y that the inform	nation herein cor	ntained is true an	nd complete to the	bes of my knowledge.	
oil:emarks: nereby certif	BOPD y that the inform	nation herein cor	ntained is true an	nd complete to the	bes of my knowledge.	

A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion.

Such tests shall also be previously shall also be

by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.

- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).