

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
PO Box 4289, Farmington, NM 87499
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1520'N, 1530'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☒
☐
☐
☐
☐
☐
☐
☐


5. LEASE
SF 078483A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Allison Unit
8. FARM OR LEASE NAME
Allison Unit Com
9. WELL NO.
60
10. FIELD OR WILDCAT NAME
Blanco Mesa Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
sec. 26, T-32-N, R-7-W, NMPM
12. COUNTY OR PARISH
San Juan
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
6520' GL

RECEIVED

OCT 18 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-13-82 PBSD 6189'. Tested casing to 3500#, OK. Perforated 5769', 5779', 5785', 5791', 5797', 5803', 5809', 5812', 5822', 5832', 5838', 5859', 5874', 5886', 5896', 5903', 5920', 5941', 5986', 6019', 6039', 6094', 6123' with 1 spz. Fraced with 62,500# 20/40 sand and 140,330 gal. treated water. Flushed with 14,952 gal. water.

Perforated 5412', 5466', 5494', 5509', 5517', 5582', 5613', 5672', 5682', 5695', 5701', 5729' with 1 spz. Fraced with 31,500# 20/40 sand and 69,920 gal. treated water. Flushed with 7220 gal. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Deane Bradford TITLE Drilling Clerk DATE October 18, 1982

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT 19 1982