

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well other

2. NAME OF OPERATOR

Consolidated Oil & Gas, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 2038, Farmington, N.M. 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1520' FNL & 790' FEL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

(other) "Drilling Operations" X

5. LEASE

SF 078464

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Cain

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

WC Pic.Cliffs/Fruitland

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 25, T31N, R13W

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

14. API NO.

30-045-25574

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5820'GR, 5824'KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-19-83 Drilling ahead.

2-20-83 Drilled 6-1/4" hole to 2205'KB, total depth. Circulate & condition hole. Ran DILL, FDC/CNL/GR, SP, & Caliper logs. Ran 4-1/2", 10.5#, ST&C, K-55 new casing & set @ 2203'KB. Cemented w/ 428 cu ft 65/35 poz w/ 6% gel & 1/2 cu ft perlite/sk. Followed w/ 184 cu ft 50/50 poz w/ 2% gel. Good circulation. Circ 5 bbls cmt to surface. Plug down @ 2230 hrs.

2-21-83 Rig released @ 0030 hrs.

(FC @ 2159')

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dakara C. Key TITLE Prod. & Drlg. Tech.

DATE 2-23-83

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY.

TITLE

DATE

ACCEPTED FOR RECORD

NMOCC

FAPM/GCH/5,8107

