

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 3249, Englewood, CO 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 700' FNL, 1800' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

AUG 29 1983

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

5. LEASE

SF-079691

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gelbke Com

9. WELL NO.

1E

10. FIELD OR WILDCAT NAME

Baskin Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11, T31N, R11W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

14. API NO.

30-045-25603

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5883' GR

RECEIVED

NOTE: Report results of multiple completion or zone change on Form 9-330.

SEP 2 1983

OIL CON. DIV.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/13/83: SPUD @10:30 AM 8-13-83. Drill 12 1/4" hole. Run 7 jts (310') 9 5/8" 36# K-55 ST&C set @326'. cmt w/300 sx (354 cf) cl-B +2% CaCl₂ + 1/4#/sx D-29. circ 10 bbls to surf. NUBOP, pt to ~1000 psi, 20 min. ok.

8/19/83: TD 8 3/4" hole @10:30 AM 8-19-83, run 64 jts 7" 23# K-55 LT&C & 60 jts 7" 23# K-55 ST&C csg(total 4781') set @4770', DV @2004' cmt 1st stage w/245 sx (453 cf) 65:35 lite POZ + 1/4#/sx D-29, tail w/150 sx (177 cf) CL-B+ 1/4#/sx D-29 +2% CaCl₂ no cmt circ

8/20/83: Ran temp survey, TOC 400'

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

John A. [Signature]

TITLE Production Analyst DATE

8/24/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

AUG 31 1983

*See Instructions on Reverse Side

NMOCC

FARMINGTON RESOURCE AREA

BY

[Signature]

Instructions

General: This form is designed for submitting proposals to perform certain well operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

8/22/83: TD 6-1/4" hole @8:15 AM 8-22-83. TD 7181',
Run 5 jts 4-1/2" 11.6# K-55 LT&C 7 57 jts
4-1/2" 10.5# K-55 ST&C csg (total 2590')
Set @ 7181'. TOL @4584'. CMT W/150 sx
(277 cft) 65:35+ 6% ge1 + 1/4#/sx D-29
+6%D-60 tat1 W/150 sx (177 cft) CL-B
+6% D-60 + 1/4#/sx D-29. Trace of CMT
to surface Rig Release @ 2 AM 8-23-83.

4/5