

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate  
(Other instructions on re-  
verse side)

Form approved  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. NAME OF OPERATOR Tenneco Oil Company	3. ADDRESS OF OPERATOR P. O. Box 3249, Englewood, CO 80155	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1030' FNL, 840' FWL	14. PERMIT NO.	15. ELEVATIONS (Show whether SP, ST, GR, etc.) 6213' GR
--	--	---	--	----------------	--

5. LEASE DESIGNATION AND SERIAL NO. SF-080917	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME Atlantic	9. WELL NO. 1E	10. FIELD AND POOL, OR WILDCAT Basin Dakota	11. SEC., T., R., N., OR S.E. AND SURVEY OR AREA Sec. 34, T31N, R10W	12. COUNTY OR PARISH San Juan	13. STATE NM
--	--------------------------------------	------------------------	-----------------------------------	-------------------	--	--	----------------------------------	-----------------

RECEIVED  
AUG 09 1984

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other)	<input type="checkbox"/>
(Other)	<input type="checkbox"/>		
PULL OR ALTER CASING	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
MULTIPLE COMPLETS	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
CHANGE PLANS	<input checked="" type="checkbox"/>		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Tenneco requests permission to change the drilling procedure on the referenced well according to the attached drilling procedure.

RECEIVED  
AUG 15 1984  
OIL CON. DIV.  
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED

*Scott McKinnis*

TITLE Sr. Regulatory Analyst

DATE 8/6/84

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

NMOCC

\*See Instructions on Reverse Side

APPROVED

AUG 13 1984

DATE

/s/ J. Stan McKee

AREA MANAGER  
FARMINGTON RESOURCE AREA

Doc 1830M

TENNECO OIL COMPANY  
WESTERN ROCKY MOUNTAIN DIVISION  
6162 SOUTH WILLOW DRIVE  
ENGLEWOOD, COLORADO 80155

DRILLING PROCEDURE

DATE: July 24, 1984

LEASE: Atlantic WELL NO: # 1E

LOCATION: 1030' FNL, 840' FWL FIELD: Basin Dakota  
Section 34, T31N, R10W  
San Juan County, NM

ELEVATION 6,213'

TOTAL DEPTH: 7,620'

PROJECTED HORIZON: Dakota

SUBMITTED BY: Mark Kangas

DATE: July 24, 1984

APPROVED BY: *Mark Kangas*

DATE: 7-24-84

CC: Administration  
CRJ Well File  
Field File

ESTIMATED FORMATION TOPS

Ojo	1535'	Water
Kirtland	1635'	
Fruitland	2525'	Coal, Gas
Pictured Cliffs	2930'	
Lewis	3025'	
Cliff House	4650'	Potential Lost Circulation Zone
Menefee	4745'	
Point Lookout	5230'	Potential Lost Circulation Zone
Mancos	5455'	
Gallup	6485'	
Greenhorn	7250'	
Dakota	7365'	Gas
TD	7620'	

### DRILLING, CASING AND CEMENT PROGRAM

1. MIRURT. Notify MMS of spud.
2. Drill a 12-1/4" hole to  $\pm$  300 ft. with a gel water mud.
3. Rig up and run 9-5/8" 36# K-55 ST&C casing to bottom. Cement with Class B + 2%  $\text{CaCl}_2$  in sufficient quantity (200-250sx) to circulate cement to surface. If conditions warrant the use of loss circulation agents, 1/4 #/sx celloflake may be added. Wait on cement a minimum of 12 hours prior to drilling out.
4. While waiting on cement, screw on a 9-5/8" -8rd X 11-3M casinghead. NU BOP's. Pressure test casing, blinds, manifold and lines to 1000 psi for 30 minutes. GIH with drill pipe and test the pipe rams in the same manner. Record all tests on the IADC report sheet.
5. Drill out with an 8-3/4" bit and clear water. Drill to  $\pm$  3525' or 500' into the Lewis Shale. Mud up prior to reaching intermediate T.D. Circulate at casing point a sufficient time to clean the hole to run casing. GE's may decide to log intermediate hole.
6. Install casing rams, run 7" 23# K-55 casing equipped with a guide shoe on bottom, float collar one joint up and a stage collar at 3100'. Bakerlock from the shoe to the top of the float collar and run casing to bottom. Centralize casing with one centralizer in the middle of shoe joint and then on every other collar for total of 6 centralizers. Place one centralizer above and below the stage tool. Cementing baskets below the DV tool may be used if lost circulation has been encountered.

### INTERMEDIATE CEMENTING PROGRAM

<u>FIRST STAGE</u>	<u>LEAD</u>	<u>TAIL</u>
Type	Lite + 1/4 #/sx flocele + 2% $\text{CaCl}_2$	C1 B + 1/4 #/sx flocele + 2% $\text{CaCl}_2$ .
Sacks		150-200 sx
Slurry yield	1.84 cu ft/sx	1.18 cuft/sx
Mix weight	12.7 ppg	15.6 ppg
Water req's.	9.9 gal/sx	5.20 gal/sx

SECOND STAGE	LEAD	TAIL
Type	Lite + 1/4 #/sx flocele + 2% CaCl <sub>2</sub>	C1 B + 2% CaCl <sub>2</sub>
Sacks	Calculated annular volume	50-75
Slurry yield	1.84 cuft/sx	1.18 cuft/sx
Mix weight	12.7 ppg	15.6 ppg
Water req's.	9.9 gal/sx	5.2 gal/sx

Precede the first stage with 20 bbls chemical wash and circulate four hours after opening the stage tool. Precede the second stage with 10 bbls "flow-check" or equivalent. If cement is not circulated to surface run a temperature survey after 8 hours to determine actual TOC as MMS requires. Wait on cement a total of 18 hours (from first plug down) before drilling is resumed.

7. Set slips with casing in full tension and cut-off. NU BOE and test as in procedure 4 above. Record tests on IADC report.
8. Drill out, dry up hole and drill a 6-1/4" hole , with air, to T.D. surveying as required. Lay down square drill collar before cutting the Dakota. Should dusting operations cease due to Gallup oil flow, be prepared to start injection of stable foam as the circulating medium. If this technique fails, prepare for an aerated mud system.
9. Log open hole as directed by GE department.
10. If productive, run 4-1/2" 11.6# and 10.5# K-55 casing as a liner. Equip the casing with a float shoe and both a float collar and latch down collar on the top of the first joint. No threadlock or centralizers are to be used on this arrangement. Hang liner with a 150' lap in the intermediate casing.
11. Cement with a filler slurry as used for the intermediate string. Start with a 20 barrel mud flush, followed by the lead slurry with a fluid loss control additive and tail with 100 sx C1 B. Use sufficient quantity (70-75% excess) to circulate cement to the liner top.
12. Circulate out the excess cement, LDDP and MORT.
13. In non-productive, P & A as required by USGS.
14. Install tree and fence remainder of reserve pit.

### CASING PROGRAM

<u>INTERVAL</u>	<u>LENGTH</u>	<u>SIZE</u>	<u>WEIGHT</u>	<u>GRADE</u>	<u>OPTIMUM MAKE-UP TORQUE</u>
0-300	300	9-5/8	36. #	K-55	STC 4230
0-3525	3525	7	23. #	K-55	STC 3090 LTC 3410
3375-7000	3625	4-1/2	10.5#	K-55	STC 1460
7000-7620	620	4-1/2	11.6#	K-55	STC 1700 LTC 1800

### MUD PROGRAM

0-300'	Spud mud.
300-3525'	Low solid, fresh water mud. (Water and Rapid Mud.) Mud up prior to running casing.
3525'-T D	Air and/or Stable Foam. Initial stable foam criteria at 6200' $\pm$ includes injection rate of 500 scfm at 400 psig with 10.5 gal/minute of fluid. Projected criteria at TD includes 1250 scfm at 600 psig with 11.2 gal/minute of fluid.

### EVALUATION

#### Cores and DST's:

NONE.

#### Deviation Surveys

1. Survey surface hole at 100' intervals. Maximum allowable deviation at 500' is 1-1/2°
2. From surface to the Mancos formation, deviation surveys must be taken every 500'. In the Mancos/Gallup zones, surveys to be each 250'. Record all surveys in IADC Report book. Maximum allowable change in deviation is 1° per 100'. Maximum deviation allowable is 5°.

#### Samples:

As requested by Wellsite Geological Engineer

Logs:	1. GR/INDUCTION	T D to Intermediate
	2. CDL/GR/CALIPER	T.D. 2000' Minimum

### BLOWOUT EQUIPMENT

11" - 3000 BOP with rotating head to comply with TOC requirements as shown in BOE arrangement, Figure C. Preventers must be checked for operation every 24 hours with each check recorded on the IADC Drilling Report Sheet.

## REPORTS

Drilling Reports for the past 24 hours will include depth, footage, time distribution, activity breakdown, mud properties, bit record, bottom hole assembly, types of logs and depths ran, daily and cumulative mud cost, deviation surveys, and other pertinent information to be called into Division Office by 7:30 AM Monday thru Friday.

TENNECO OIL COMPANY  
P.O. Box 3249  
ENGLEWOOD, COLORADO 80155  
PHONE: 303-740-4800

## OFFICE DIRECTORY

Charles R. Jenkins	740-2575
Ted McAdam	740-2576
Tom Dunning	740-4813
Mark Kangas	740-4810

In case of emergency or after hours call the following in the preferred order.

(1)	Mark Kangas	740-4810	Office
	Senior Drilling Engineer	973-8846	Home
(2)	Ted McAdam	740-2576	Office
	Drilling Engineering Supervisor	978-0724	Home
(3)	Charles R. Jenkins	740-2575	Office
	Division Drilling Engineer	987-2290	Home
(4)	Harry Hufft	771-5257	Home
	Division Production Manager		