

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

OIL COM. DIV. Revised 100 DIST. 3

This form is not to be used for reporting packer leakage tests in Southeast New Mexico 1997

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| Operato | r | CHATEAU OIL | & G2 | AS, INC. | Lease | PAYNE | | Well 3E | |
|---------------------|---------------------------|-------------|----------------------------|---------------------------|------------------------|-----------------------------|--------------------|-------------------------------|--|
| Location of Weil: | Unit | D Sec. 26 | _ Tw | p31N | Rgc. | 13W | Cor | unty SAN JUAN | |
| | NAME OF RESERVOIR OR POOL | | | | TYPE O | TYPE OF PROD. (Oll or Gas) | | Do. PROD. MEDIUM | |
| Upper Completion | | GALLUP | | | GAS | GAS | | TBG | |
| Lower Completion | | | | | GAS | | FLOW | TBG | |
| | | | | PRE-FI | OW SHUT-IN | PRESSURE DAT | Α | | |
| Upper | Upper j | | | | Length of time shut-in | | | Stabilized? (Yes or No) | |
| Completion | | | | 3 days | | 425 | | NO Stabilized? (Yea or No) | |
| Lower Completion | - 10- | | | Length of time and 3 days | ut-in | SI press. paig 295 | | no | |
| | | | | <u> </u> | FLOW TEST | | | | |
| Continenced | at (hour, di | 16)* 7/30 | | | 120 11 120 1 | Zone producing (L | poer or Lowert | lower | |
| | TIME LAI | | PRESSU Upper Completion | | SURE Lower Completion | PROD. ZONE TEMP. | | REMARKS | |
| 7/28 | | | 300/90 | | 185 | | Both zones shut in | | |
| 7/29 | | | 390/385 | | 275 | | Both zones shut in | | |
| 7/30 | | | 430/425 | | 295 | | Both | zones shut in | |
| 7/31 | | 1 day | 455/455 | | 100 | | Flowing lower zone | | |
| 8/1 | | 2 days | - 4 | 80/480 | 100 | | Flowing lower zone | | |
| | • | | | | | | | | |
| roduction | rate di | uing test | | | | | | | |
|)il: | | ВОРГ | bas | ed on | Bbls. in | Hours | Gr | av GOR | |
| ias: | s:52 | | | | MCFPD; Tested thru (| | ·): | TER | |
| | | | | MITD-TTES | ST SHUT-IN PR | ESSURE DATA | | | |
| Upper empietion | ur, gale sh | ut-in | L | ength of time shut- | | I press. psig | | Stabilized? (Yes or No) | |
| Hour, gate shul-in | | | L | angth of time shut- | in : | press, paig Stabilized? (Ye | | tabilized? (Yes or No) | |

| and the second section is | | 33.5 | | FLOW TEST | NO. 2 | | | | |
|---------------------------|---|---------------------------------|------------------|-------------------|----------------------|---------------|-----|--|--|
| Commenced at (hour, da | 1(e)** ~ * | Zone producing (Upper or Lower: | | | | | | | |
| TIME | LAPSED | | | SURE | PROD. ZONE | REMARKS | | | |
| (hour, date) | | ** | Upper Completion | Lower Completion | TEMP. | | | | |
| ļ | | | | | | · | | | |
| · | | | | | | | | | |
| | | | | | | · | | | |
| | | | · | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| Production rate d | uring test | 1 | | • | | | · | | |
| • | | BOPD based onBbi | | | Hours | G12v | GOR | | |
| Gas: | | | MCFF | D: Tested thru (| Orifice or Meter): | | | | |
| Remarks: | *************************************** | | | | | | | | |
| | | | | | | | | | |
| hereby certify the | at the info | rmation | herein containe | d is true and com | plete to the best of | ny knowledge. | | | |
| Approved | | 1 | | | CHATEAN | OTT COAC IN | c | | |
| New Mexico Oil | | | | . 19 O p | 1/4 / 6/ | laste | | | |
| | | ł | | Ву | erztor CHATTAGO | weer - | | | |
| Sv. | my o | Kolu | noun | Tiri | | ON ANALYST | · | | |
| By Dep | puty Oil & | Gas Ir | spector | | 2/18/9 | | _ | | |
| Tide | | | | Dat | $= \frac{2/18/3}{2}$ | / b | | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the pacet time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall comments when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completing of Flow Tow Ma. 1. sha wall shall seem be churcin, in secure

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the begins ing of each flow-period, at fifteen-minute intervals during the first hour thereof, and a hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period. at least one time during each flow period (at approximately the midwa point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days afte completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Reviser 10.01.78 with all deadweight pressures indicated thereon as well as the flowing