

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. Gallup Dakota OIL WELL <input checked="" type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. NM 40649
2. NAME OF OPERATOR JEROME P. McHUGH	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P O Box 809, Farmington, NM 87499	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 810' FNL - 1830' FEL	8. FARM OR LEASE NAME Pump Canyon B
14. PERMIT NO.	9. WELL NO. 5
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6020' GL; 6035' RKB	10. FIELD AND POOL, OR WILDCAT Basin Dakota & La Plata Gallup
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 5, T31N, R13W, NMPM
	12. COUNTY OR PARISH San Juan
	13. STATE NM

15. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PLUG OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

PER VERBAL APPROVAL OF JOHN KELLER 7/26/85 P.M.

Well was plugged and abandoned 7/27/85 as follows:

Set 100' plug with 30 sx class "B" (35.4 cf) from 3980 to 3880' KB.

Plug down at 8:00 AM 7/27/85.

Set 100' plug with 45 sx class "B" (53.1 cf) from 3006 to 2906' KB.

Plug down at 9:30 AM 7/27/85.

Set 100' plug with 60 sx class "B" (70.8 cf) from 810 to 710' KB.

Plug down at 11:30 AM 7/27/85.

Set plug from 406' to surface with 195 sx class "B" (230.1 cf).

3 bbl. cement circulated to surface at 12:00 noon 7/27/85.

Plan to set marker 8/1/85. Plan to clean and restore location as required by the surface management agency.

18. I hereby certify that the foregoing is true and correct

SIGNED

James S. Hazen

TITLE

Field Supt.

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUL 31 1985

OIL CON. DIV.

APPROVED
DATE 7/29/85

DATE JUL 30 1985

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side