State of New Mexico Energy, Minerals and Natural Resources Department Oil Conservation Division

Sundry Notices and Reports on Wells	
	API # (assigned by OCD) 30-045-26906
1. Type of Well GAS	5. Lease Number
GAU	6. State Oil&Gas Lease #
2. Name of Operator BURLINGTON	Lease Name/Unit Name
	EPNG Com C
3. Address & Phone No. of Operat PO Box 4289, Farmington, NM	VIIII IIVONIVI -
4. Location of Well, Footage, Se	
_	2-N, R-10-W, NMPM, San Juan County, NM
Type of Submission	Type of Action
X Notice of Intent	Abandonment Change of Plans Recompletion New Construction
Subsequent Report	Plugging Back Non-Routine Fracturing Casing Repair Water Shut off
Final Abandonment	Altering Casing Conversion to Injection _X_ Other - Pump Installation
13. Describe Proposed or Compl	leted Operations
It is intended to install procedure and wellbore dia	a pump in the subject well according to the attached agram.
SIGNATURE SAGAY STANK	Regulatory Administrator August 2, 1999
í	trc
(This space for State Use)	
ORIGINAL SIGNED BY CHARLIE	T. PERFORM Title GEPUTY OIL & GAS INSPECTOR, DIST. #Sate AUG 1 0 1999

EPNG Com C #100 PUMPING UNIT INSTALLATION PROCEDURE 7/28/99

Unit K, Section 16, T32N, R10W, San Juan County, New Mexico Aircare Lat. 36 58.97' Aircare Long. 107 53.44'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU AT LEAST 2 JTS. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 3503', THERE ARE 113 JTS. OF 2-3/8" 4.7# J-55 WITH F NIPPLE @ 3471').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 3530'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(3520'-3530'), 2-3/8"x6' PUP JOINT(3514'-3520'), 2-3/8"x4' PERFORATED SUB(3510'-3514') AND 2-3/8" SN @ 3510'.
- 8. HANG TBG, IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE 1-1/4" SINKER BARS, 138 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2',4',6',8') TO SPACE OUT, ONE 1-1/4"x 22 3/4" PIN POLISHED ROD AND ONE 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles

Office: 326-9584 Home: 325-8164 Pager: 324-2636 Approved: Drilling Supt.

Pump Company is Energy Pump & Supply

(505)564-2874

EPNG COM C #100

(Current)

Cedar Hill Fruitland Basal Coal Unit K, Section 16, T32N, R10W, San Juan County, New Mexico

