Forta 3160-5 (November 1983) (Formerly 9-331)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		Form approved. Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL RO. SF-078215
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			6. IF INDIAN, ALLOTTES OR TRIBE NAME
OIL GAS WELL WELL W	OTESE		T. UNIT AGREEMENT NAME
2. HAME OF OPERATOR			S. PARM OR LEASE NAME
Southland Royalty Company			Page
			9. WELL NO.
Post Office Box 4289, Farmington, NM 87499 4. Location of Well (Report location clearly and in accordance with any State requirements.)			101
See also apace 17 below.) At surface 910 'S, 510 'W			10. PIELD AND POOL, OR WILDCAT
510 B, 510 W			Basin Fruitland Coal
			Sec. 18, T-32-N, R-10-W
			N.M.P.M.
14. PERMIT NO.	15. SLEVATIONS (Show whether DF.	ET, GR. etc.)	12. COUNTY OR PARISH 13. STATE
	618	7'GL	San Juan NM
16.	Check Appropriate Box To Indicate No	sture of Notice Person of O	the De-
	CE OF INTENTION TO:		•
į		********	INT ABPORT OF:
TEST WATER SHUT-OFF	PCLL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT SHOOT OR ACIDIZE	MULTIPLE COMPLETE	PRACTURE TREATMENT	ALTERING CASING
REPAIR WELL	ABANDON* CHANGE PLANS	SHOOTING OR ACIDIZING	oud Well
(Other)		NOTE: Report require	of multiple completton on Well
7. SESCRIBE PROPUSED OR CON proposed work. [f wei nent to this work.] *	PLETED OPERATIONS (Clearity state all pertinent is directionally drilled, give subsurface location	d-4	tion Beport and Log form.) nciuding estimated date of starting any depths for all markers and sones perti-
12-08-88	Spudded well at 4:30 pm 12-08-88. Drilled to 223'. Ran 5 jts. 9 5/8", 32.3#, H-40 surface casing set at 223'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (177 cu.ft.). circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.		
12-10-88 M.C. S. S. H. C. S. S. S. H. C. S.	TD 2674'. Ran 70 jts. 2663' set @ 2674'. Cerwith 6% gel, 2% calcium cu.ft.) followed by 10 chloride (118 cu.ft.). Circulated to surface.	mented with 380 sk m chloride, 1/2 ct 0 sx. Class "B" wi WOC 12 hours. Hel	ks. Class "B" 65/35 1.ft. perlite/sx (733 ith 2% calcium ld 1200#/30 min.
FARMINGTON NEW PEXICO	,		

*See Instructions on Reverse Side

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

BY KU

ACCEPTED FOR RECORUM

FARMINGTON RESOURCE ARE