## UNITED STATES DEPARTMENT OF THE INTERIOR

•	ices and Reports on We	ells	*
1. <b>Type of Well</b> GAS		5. Note 2 1 1999 Note 1 5 1989	Lease Number SF-080376-A If Indian, All. or Tribe Name
2. Name of Operator		CON. DIV.	Unit Agreement Name
BURLINGTON RESOURCES OIL	& GAS COMPANY	endie 3	Well Name & Number
3. Address & Phone No. of Operator		<b>—</b> .	Sheets #250
PO Box 4289, Farmington, NM 87499 (505) 326-9700		9.	API Well No.
4. Location of Well, Footage, S 1135'FSL 1840'FEL, Sec.28, T			30-045-26923 Field and Pool Basin Fruitland Coa County and State San Juan Co, NM
12. CHECK APPROPRIATE BOX TO IN	DICATE NATURE OF NOTIC	E, REPORT, OTHER	DATA
Type of Submission	Type of A	ction	
_X_ Notice of Intent	Abandonment	Change of Pl	
	$\_\_$ Recompletion	New Construc	
Subsequent Report	Plugging Back	Non-Routine	_
Final Abandonment	<pre> Casing Repair Altering Casing _X_ Other -</pre>	Water Shut o	
13. Describe Proposed or Comp  It is intended to install procedure and well	a pump in the subject	well according	to the attached
<u></u>			
			RECEIVED BLM 99 MAR -4 PH 2: 34 070 FAGMENGTON, NN

\_\_\_\_\_Title Acting lam Lad Date 3/11/99 APPROVED BY Charader CONDITION OF APPROVAL, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(This space for Federal or State Office use)

## Sheets #250 **PUMPING UNIT INSTALLATION PROCEDURE** 2/25/99

## Unit O, Section 28, T31N, R09W, San Juan County, New Mexico Aircare Lat. 36 51.90' Aircare Long. 107 46.96'

- 1. MIRU PULLING UNIT.
- 2. BLOW DOWN TBG. KILL WELL W/ WATER ONLY IF NECESSARY.
- 3. NDWH / NUBOP.
- 4. PU AT LEAST 1 JT. OF TBG. TIH TO TAG FOR FILL.
- 5. TOH STANDING BACK 2-3/8" TBG. (TBG. IS SET @ 2959', THERE ARE 93 JTS. OF 2-3/8" 4.7# J-55 WITH F NIPPLE @ 2926').
- 6. PU 4-3/4" BIT ON 2-3/8" TBG. AND TIH TO COTB, CIRC. HOLE CLEAN. TOH W/ SAME.
- 7. TIH W/ 2-3/8" TBG. STRING AND LAND TBG. @ 2982'. PURGE VALVE WILL BE ON BOTTOM W/ 2-3/8"x10' PUP JOINT(2972'-2982'), 2-3/8"x6' PUP JOINT(2966'-2972'), 2-3/8"x4' PERFORATED SUB(2962'-2966') AND 2-3/8" SN @ 2962'.
- 8. HANG TBG. IN DONUT. NDBOP / NUWH.
- 9. TIH W/ NEW TOP HOLD DOWN ROD PUMP (2"x1-1/4"x10'x14' RHAC-Z), 4' SECTION CUP TYPE PLUNGER. RUN THREE - 1-1/4" SINKER BARS, 116 - 3/4" GRADE D SUCKER RODS (W/ SPRAY METAL COUPLINGS), A SET OF 3/4" PONY RODS (2',4',6',8') TO SPACE OUT, ONE - 1-1/4"x 22 - 3/4" PIN POLISHED ROD AND ONE - 1/1/4"x1-1/2"x10' POLISHED ROD LINER.
- 10. SEAT THE DOWNHOLE PUMP, HANG HORSES HEAD ON, SPACE PUMP.
- 11. LOAD TBG., PRESSURE TEST.
- 12. START PUMPING UNIT, AND TEST OK (ADJUST SPACING IF NEEDED).
- 13. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

Prepared: E.J. Giles

Office: 326-9584 Home: 325-8164 Pager: 324-2636

Druce U. Boy 3.1.99
Approved: Drilling Stept.

## Sheets #250 (Current) Basin Fruitland Coal Unit O, Section 28, T31N, R9W, San Juan County, New Mexico

