

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1240' FNL, 1120' FEL, Sec. 19, T-32-N, R-6-W, NMPM, San Juan County, NM

API # (assigned by OCD)

30-045-27172

5. Lease Number

Fee

6. State Oil&Gas Lease #

7. Lease Name/Unit Name

Allison Unit

8. Well No.

#114

9. Pool Name or Wildcat

Basin Fruitland Coal

10. Elevation:

Type of Submission

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment

Type of Action

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other - Pump Installation

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off


☐ Conversion to Injection

13. Describe Proposed or Completed Operations

It is intended to install a pump in the subject well according to the attached procedure and wellbore diagram.

RECEIVED
SEP - 9 1999
OIL CON. DIV.
DIST. 3

SIGNATURE



Regulatory Administrator

September 7, 1999

trc

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PERSON

DEPUTY OIL & GAS INSPECTOR, DIST. 3

SEP - 9 1999

Approved by

Title

Date

Allison Unit #114
PUMPING UNIT INSTALLATION PROCEDURE
7/15/99

Unit I, Section 19, T32N, R6W, San Juan County, New Mexico
Lat. 36.969635 / 36° 58.18'
Long. 107.494629 / 107° 29.68'

1. MIRU pulling unit.
2. NDWH / NU BOP. NOTE: Blow well dead. Kill if necessary with produced Fruitland coal water.
3. PU one joint of tubing and TIH to tag for fill.
4. TOH standing back 99 joints of 2-3/8", 4.7#, J55 tubing set @ 3115'. F nipple @ 3081'.
5. PU 4-3/4" bit on tubing and TIH to COTD at 3149'. Circulate hole clean.
6. TIH w/ 2-3/8" tubing string configured for downhole pump and land at 3145'. Purge valve will be on bottom, followed by pup joint, perforated sub, and seating nipple. Space out as needed with pup joints.
7. Hang tubing in donut. ND BOP / NUWH.
8. TIH w/ new 1.25" top hold down pump, 3/4" Grade D sucker rods w/ spray metal couplings, polished rod, and polished rod liner. (Note: Vendor contact is listed below)
9. Seat the downhole pump, hang horses head, and space out pump.
10. Load tubing, and pressure test ~~to~~ **500 psi.**
11. Start pumping unit and test (adjust spacing as required).
12. RDMO.

COMPLY WITH ALL FEDERAL, STATE AND LOCAL RULES AND REGULATIONS RELATING TO OIL AND GAS OPERATIONS.

S. T. Portra

Prepared: S. T. Portra

WMM

Pump vendor: ENERGY PUMP
Leo Noyes @ 564-2874

Bruce D. Bony 8.22.99

Approved: Drilling Supt.

Allison Unit #114

Basin Fruitland Coal

Unit A, Section 19, T32N, R6W, San Juan County, New Mexico

Completed: 1/15/89

Note: 3/4" sucker rods and
downhole pump assembly
will be run.

Ojo Alamo @ 2300'

Kirtland @ 2385'

Fruitland @ 2965'

Perforations: 3059-3148'

