

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO.

30-045-27424

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-5386, B-11370, E-3150

7. Lease Name or Unit Agreement Name

PUBCO STATE COM

8. Well No.

3

9. Pool name or Wildcat

Blanco Pictured Cliffs Ext.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐

GAS WELL ☒

DRY ☐

OTHER ☐

b. Type of Completion:

NEW WELL ☒

WORK OVER ☐

DEEPEN ☐

PLUG BACK ☐

DIFF RESVR ☐

OTHER ☐

2. Name of Operator

GREAT WESTERN DRILLING CO.

3. Address of Operator

2550 La Plata Hwy, Farmington, NM 87401

4. Well Location

Unit Letter J: 1535 Feet From The South Line and 1640 Feet From The East Line

Section

36

Township

31N

Range

11W

NMPM

San Juan

County

10. Date Spudded

9-26-89

11. Date T.D. Reached

10-1-89

12. Date Compl. (Ready to Prod.)

11-10-89

13. Elevations (DF & RKB, RT, GR, etc.)

5928 GR

14. Elev. Casinghead

Same

15. Total Depth

2730

16. Plug Back T.D.

2687

17. If Multiple Compl. How Many Zones?

18. Intervals Drilled By

Rotary Tools

Cable Tools

X

19. Producing Interval(s), of this completion - Top, Bottom, Name

2556-2647 Pictured Cliffs

20. Was Directional Survey Made

every 500'

21. Type Electric and Other Logs Run

Gamma Ray Neutron, Compensated Density w/Caliper & Temp

22. Was Well Cored

No

23.

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8-5/8"	24	265	12 1/2"	200 sx class "B" cement circulated	
2-7/8"	6.5	2730	6-3/4"	150 sx class "G" + 2% CaCl ran Temp	Sur.
Found top of cement outside @ 2000' 10-4-89 ran 1' outside & brought cement to surface.					

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN
NONE				

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET

26. Perforation record (interval, size, and number)

2556-74, 2576-82, 2614-22, 2627-34, 2641-47

1 SPF

.40 I.D. total 44 holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL

AMOUNT AND KIND MATERIAL USED

2556-2647

10 gals 7 1/2% HCL acid

53,000 gals slick water

45,000 lbs 20/40 sand

28. PRODUCTION

Date First Production

Production Method (Flowing, gas lift, pumping - Size and type pump)

Well Status (Prod. or Shut-in)

S.I. W.O. pipeline

Date of Test	Hours Tested	Choke Size	Prodn For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
1-3-90	3	3/4"		"0"	1682.2	"0"	
Flow Tubing Prod.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gravity - API - (Corr.)	
Tubingless	718 PSI		"0"	1682.2	"0"	gas 6.5 (assumed)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Vented

Test Witnessed By B.W. Hampton

B. W. Hampton

30. List Attachments

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature

D.E. Baxter

Printed

Name Doyle Baxter

Title Dist. Supt.

Date 1-3-90

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

Southeastern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	1150	T. Penn. "B"
T. Salt	T. Strawn	T. Kirland-Fruitland	2187	T. Penn. "C"
B. Salt	T. Atoka	T. Picured Cliffs	2495	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House		T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee		T. Madison
T. Queen	T. Silurian	T. Point Lookout		T. Elbert
T. Grayburg	T. Montoya	T. Mancos		T. McCracken
T. San Andres	T. Simpson	T. Gallup		T. Ignacio Ortiz
T. Glorietta	T. McKee	Base Greenhorn		T. Granite
T. Paddock	T. Ellenburger	T. Dakota		T.
T. Blinebry	T. Gr. Wash	T. Morrison		T.
T. Tubb	T. Delaware Sand	T. Todillo		T.
T. Dinkard	T. Bone Springs	T. Entrada		T.
T. Abo		T. Wingate		T.
T. Wolfcamp		T. Chinle		T.
T. Penn		T. Pernaian		T.
T. Cisco (Bough C)		T. Penn "A"		T.

No. 1, from	to	No. 3, from	to
No. 2, from	to	No. 4, from	to

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	10	feet
No. 2, from	10	feet
No. 3, from	10	feet

From	To	Thickness in Feet	Lithology
From	To	Thickness in Feet	Lithology