

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-045-27427
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. 14-08-001-1201
7. Lease Name or Unit Agreement Name J. E. Decker
8. Well No. 10
9. Pool name or Wildcat Basin Coal
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6479 GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator GREAT WESTERN DRILLING CO.
3. Address of Operator 2550 La Plata Hwy Farmington, NM 87401
4. Well Location Unit Letter <u>K</u> : <u>1690</u> Feet From The <u>South</u> Line and <u>1775</u> Feet From The <u>West</u> Line Section <u>7</u> Township <u>32N</u> Range <u>11W</u> NMPM <u>San Juan</u> County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6479 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLUGS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Drill Fruitland Coal Section ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-5-89

Move in completion rig, set up and test B.O.P. & 7" csg. to 1450 PSI 15" held o.k.
drill float collar and float shoe @ 2773', drill Fruitland Coal section 2773 to 2976'
ran logs, Comp-Dent, GR-N, & EPL w/caliper, ran 8 jt's 4 1/2" J-55, set w/Baker 7" liner
hanger, top of liner 2646', bottom @ 2975', cemented w/50 sx 50/50 Posmix 2% gel +
2% CaCl, cement circulated, reversed out 3 bbl. cement, W.O.C. 12 hrs., ran cement
bond log, clean out inside 4 1/2" liner to 2971', perforate 4 1/2" liner 2801-2963',
106 holes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE D. E. Wrayles TITLE Superintendent DATE February 9, 1990
TYPE OR PRINT NAME TELEPHONE NO.

(This space for State Use)

APPROVED BY Original Signed by FRANK T. CHAVEZ TITLE SUPERVISOR DISTRICT # 3 DATE FEB 12 1990
CONDITIONS OF APPROVAL, IF ANY: