Form 3160-5 (November 1983) (Formerly 9-331) UNITED STATES SUBMIT IN TRIPLICATE* (Other Instructions on re- BUREAU OF LAND MANAGEMENT	Budget Burgau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS OTHER 2. NAME OF OPERATOR	7. UNIT AGREEMENT NAME San Juan 32-7 Unit 8. FARM OR LEASE NAME
Northwest Pipeline Corporation 3. ADDRESS OF OPERATOR 1.2520 Foot 20th Street Services NM 07401	San Juan 32-7 Unit 9. WBLL NO.
. J. 3539 East 30th Street - Farmington, NM 87401 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1070' FSL & 1830' FWL SE/4 SW/4	#202 10. FIELD AND POOL, OR WILDCAT Basin Fruitland Pool 11. SEC., T., E., M., OR BLK. AND SURVEY OR ARMA
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6400 GR	Sec. 18N, T32N, R7W 12. COUNTY OR PARISH 13. STATE San Juan New Mexico
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	
PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical nent to this work.)* 10-25-89: MOL & RU. Drilled MH and RH. Spudded well at 1600 ht (211') 9-5/8", 32.3#, H-40, ST&C Lonestar ERW casing. Set at 22's (155 cu.ft.) Cl "B" w/ 3% CaCl and 1/4# gel flake/sk. Displace Circulated 15 bbls cement. Plug down at 2215 hrs 10/25/89. WOC	of multiple completion on Well tion Report and Log form.) including estimated date of starting any depths for all markers and zones pertins 10/25/89. Ran 5 jts 4' KB. Cemented w/ 130 aced w/ 16 bbls water.
10-27-89: Drilling w/ Benex. 10-28-89: Drilling w/ Benex. TD'd hole w/ mud. Circulated hole its (2915') 7", 23#, K-55, LT&C, CF&I smls casing. Set at 2928' Cemented w/ 330 sx (683 cu.ft.) Cl "B" 65/35 poz w/ 12% gel. Tacu.ft.) Cl "B" (75% excess to circulate surface). Displaced w/ down at 0530 hrs 10/29/89. Good circulation throughout job.	KB. FC at 2882' KB. iled w/ 75 sx (89
10-29-89: Wilson Service ran temperature survey and found TOC a	t 300'. 👸 🔠
MAR 07 1990	
OIL CON. DIV.	2
18. I hereby certify that the foregoing is true and correct SIGNED AND AND TITLE Production Assistant	DATE 1-26-90
(This space for Federal or State office use)	ACCEPTED FOR RECORD

NMOCD

TITLE .

APPROVED BY _______ CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

FARMINGTON INCOMPRENDEN.
BY 211

