Schmit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

CONTITUE STATE AFTROVAL, IP ANY:

OIL CONSERVATION DIVISION
P.O. Box 2088
Scott Fo. New Morion \$7504 2088

Revised 1-1-

Satis Fe, New Mexico 87504-2088 5. Indicate Type of Law STATE FE 1. Special Research No. 1. Sund Oil & Gill Lese No. 1. Sund Oil & Gill Lese No. 1. Sund Oil & Gill Lese No. 1. Type of Wall Oil Control USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEFEN OF PLUG BACK TOA OIL (THE PROPOSALS) TO DRILL ON TO DEFEN OF PLUG BACK TOA OIL (THE PROPOSALS) TO SUCH PROPOSALS) HE HATT O'CHE O'CH O'C	P.O. Box 2088			30-045	-27905	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO SELECT TO DEEPEN OF PULIG BACK TO A (DO NOT USE THIS FORM FOR PROPOSALS TO SELECT TO DEEPEN OF PULIG BACK TO A (DO NOT USE THIS FORM FOR PROPOSALS TO SELECT TO DEEPEN OF PULIG BACK TO A (DO NOT USE THIS FORM FOR PROPOSALS TO SELECT TO DEEPEN OF PULIG BACK TO A (DO NOT USE THIS FORM FOR PROPOSALS TO SELECT TO DEEPEN OF PULIG BACK TO A (DO NOT USE THIS FORM FOR PULIC TION OF PULIC T	P.O. Drawer DD, Artesia, NM 88210	Salita re, New Mexico 8/304-2088		5. Indicate Type of Lease STATE STATE		
(DO NOT USE THIS DEPORT FOR PROPOSALS TO DRILL OR TO DEEPEN OF PLUGATION OF PLUGATI	DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			6. State Oil & Gas		LEE ET
1. Type of Well:	(DO NOT USE THIS FORM FOR PROPOS DIFFERENT RESERVOI	SALS TO DRILL OR TO DEEPEN R. USE "APPLICATION FOR PE	OR PLUG BACK TO A	7. Lease Name or	Unit Agreement Name	
2 Name of Operator	1. Type of Well:			Mudge Ga	as Com "E"	
A Address of Operator 2550 La Plata Huy, Farmington, NM 87401 4 Well Leaune Upit Lever L : 1830 Feet From The South Line and 810 Feet From The West Line Section 23 Township 31N Runge 11W NMTM San Juan County 10. Elevation (Show whether DF, RAB, KT, GR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORABLY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND GEMENT JOB THEFE CASING TO 4½" 10.5% J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 2X CA. CL. + 4% SX. OF PERLITE, POLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2X GA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. THE ACT OF THE CASING CONTRACT OF STANDARD CONTRACT. THE ACT OF THE CASING TO SURFACE. THE ACT OF THE CASING THE C	2. Name of Operator		·			
2550 La Plata Hwy, Farmington, NM 87401 Basin Fruitland Coal GAS Well Location Unit Letter L: 1830 Feet From The South Line and 810 Feet From The West Line Section 23 Township 31N Ruspe 11W NMPM San Juan County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OF CASING TEST AND CEMENT JOB OTHER CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 51" CASING TO 41" 10.5% J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 2% CA. CL. + 4% SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIFERED, CEMENT USED TO BE 50Z OVER CALIFER AND WILL BE CIRCULATED TO SURFACE. DEC 07 IS90 CHECKED AND COMMENCE OF SURFACE.	Great Western Drilling	Company	· · · · · · · · · · · · · · · · · · ·	9. Pool name or W	 	
Well Location Unit Letter: L: 1830 Feet From The South Line and 810 Feet From The West Line Section 23 Township 31N Runge 11W NMPM San Juan County 10. Elevation (Show whether DF, RKB, RT, GR, stc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON GRAPH STORY OF PROBLEMS COMMENCE DRILLING OPNS. PLUG AND ABANDON GRAPH STORY OF PROBLEMS OF PLUG AND ABANDON GRAPH STORY OF PLUG AND ABANDON GRAPH STORY OF PROBLEMS OF	•	v. Farminoton. NM S	37401			GAs
Section 23 Township 31N Range 11W NMPM San Juan County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TO CASING TEST AND CEMENT JOB CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 531" CASING TO 43" 10.5% J-55 8rd. TO BE GEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 2% CA. CL. + 4% SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIFERED, CEMENT USED TO BE 50% OVER GAIL PER AND WILL BE CIRCULATED TO SURFACE. DEC 07 1890 CHANGE OR IGNAL SUNDRY FOR PRODUCTION CASING FROM: 51" CASING TO 45" 10.5% J-55 8rd. TO BE GEMENTED WITH 827 CU. FT. LEAD CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIFERED, CEMENT USED TO BE 50% OVER CALIFER AND WILL BE CIRCULATED TO SURFACE.	4. Well Location				-	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK		Township 31NR	-B	NMPM San	Juan ////////////////////////////////////	County
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK		(//)	NI-4 CNI : -		<u> </u>	
CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 51" CASING TEST AND CEMENT JOB CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 51" CASING TO 41" 10.5# J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 2Z CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2Z CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. DEC 07 1990 CIL CON. DIV. DIST. 3 10-5-90. THE CLASSING TO 40 CH. THE Area Supervisor. THE Area Supervisor. THE AREA CLASSING TO 4 CH. THE AREA CLASSING TO 4 CH. THE AREA CLASSING TO 4 CH. THE AREA CLASSING TO 5 SURFACE.	•••	-				
CASING TEST AND CEMENT JOB OTHER: II. Includes its proced of Completed Operations (Clearly state all periodes details, and give periodes) dates, including estimated date of stating day proposed. CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 51" CASING TO 41" 10.5# J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. DEC 07 1890 OIL CON. DIV DIST. 3 THE Area Supervisor 10-5-90. THE STATE OF MARK UNC.	PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK		ALTERING CASING	
CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 51" CASING TO 41" 10.5# J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. DEC 07 1890 CIL CON. DIV DIST. 3 100-5-90. DECOLORS AND	EMPORARILY ABANDON	CHANGE PLANS X	COMMENCE DRILLING	OPNS.	PLUG AND ABANDO	DNMENT [.
CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 5]" CASING TO 4]" 10.5# J-55 8rd. TO BE GEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. DEC 07 1890 CIL CON. DIV DIST. 3 THE CLEAN OF PERLITE FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. DEC 07 1890 CIL CON. DIV DIST. 3 THE CLEAN OF PERLITE STATES AND ST	PULL OR ALTER CASING		CASING TEST AND CE	MENT JOB		
CHANGE ORIGINAL SUNDRY FOR PRODUCTION CASING FROM: 51" CASING TO 41" 10.5# J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 67 GEL, 27 CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 27 CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE. DEC 07 1890 CIL CON. DIV. DIST. 3 THE CLUSSIONAME (Charges for Note the)	DTHER		OTHER:			
The rest of the information above is true and complete to the best of my knowledge and belief STREAM Area Supervisor THE ONLY THE ONLY THE STREAM SAME THE STREAM SAME THE STREAM SAME THE STREAM SAME	CHANGE ORIGINAL SUNDRY 5½" CASING TO 4½" 10.59 TO BE CEMENTED WITH 82 6% GEL, 2% CA. CL. + 4 118 CU. FT. + 2% CA. Cl. 7-5/8" HOLE WILL BE LO	FOR PRODUCTION CAS: # J-55 8rd. 7 CU. FT. LEAD CEMEN # SX. OF PERLITE, FO L. TOTAL CEMENT 945 GGED AND CALIPERED,	ING FROM: NT OF 65/35 POSM OLLOWED WITH 100 CU. FT. CEMENT USED TO	MIX CONSISTI) SX. REG. N	NG OF EAT DECOM	7 1990
	simon DE Bayte			sor	. DiST	. 3
						A RE 20 A
APPOVED BY	Original Signed by FRANK	T. CHAVEZ	SUPERVISOR DIS	TRICT#3	DEC	07199