Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 5. Lease Designation and Serial No. **BUREAU OF LAND MANAGEMENT** SF-078096 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well 8. Well Name and No. Oil Gas Well X Other Coal Seam Mudge "B" #59 2. Name of Operator 9. API Well No. Great Western Drilling Company 30-045-27925 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 2550 La Plata Hwy, Farmington, NM 87401 Basin Fruitland Coal 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 11. County or Parish, State 2270' FNL, 1250' FEL, NW/NE, Sec. 9, T-31N, R-11W San Juan, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION X Change of Plans Notice of Intent Abandonment New Construction ____i Recompletion Non-Routine Fracturing ____ Plugging Back Subsequent Report Water Shut-Off La Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Note: Report resorts of multiple completion on Well complete in or Recompletion Report and Log form.) 13 Describe Proposed or Completed Operations of learly state ail pertinent data, and gase pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical sleptly for all clarific and zones pertinent to this work.) CHANGE ORIGINAL APD: FOR PRODUCTION CASING: FROM: $5\frac{1}{2}$ " CASING TO $4\frac{1}{2}$ " 10.5# J-55 8rd. TO BE CEMENTED WITH 827 CU. FT. LEAD CEMENT OF 65/35 POSMIX CONSISTING OF 6% GEL, 2% CA. CL. + 4# SX. OF PERLITE, FOLLOWED WITH 100 SX. REG. NEAT 118 CU. FT. + 2% CA. CL. TOTAL CEMENT 945 CU. FT. 7-5/8" HOLE WILL BE LOGGED AND CALIPERED, CEMENT USED TO BE 50% OVER CALIPER AND WILL BE CIRCULATED TO SURFACE.

OIL CON. DIV. \ DIST. 3

A COMMUNICATION CONTINUES AND ADDRESS.

1740 10-3-90
3
De MCU AL
San GLZARIDOM PREMIDENT STATEMENT ST