

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
Meridian Oil Inc.

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
790'FNL, 1535'FEL Sec.29, T-32-N, R-10-W, NMPM

5. Lease Number
SF-078604

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
Scott #1R

9. API Well No.
30-045-28514

10. Field and Pool
Blanco MV

11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA
Type of Submission

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other - Squeeze cementing
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

02-04-93 Preceded cmt w/10 bbl mud flush, 5 BW. Displaced @ 3.5 BPM @ 50#. Unstung, dumped 2 bbl on cmt ret. Cmt ret set @ 5685'. Squeezed perfs @ 5695' & 5262' w/60 sx Class "B" w/2% calcium chloride (71 cf).

02-05-93 Unload hole w/gas @ 5100'. Precede cmt w/10 BW. Displace @ 2 BPM @ 0#, Unstung, dumped 3 bbl on cmt ret. Cmt ret set @ 5314'. Squeezed perfs @ 5351' & 5262' w/35 sx Class "B" w/2% calcium chloride (41 cf).

02-07-93 Displaced cmt to perf. Released pkr & TOOH. Unload hole w/gas prior to squeezing perfs @ 5262' w/25 sx Class "B" w/2% calcium chloride, 6.25#/sx gilsonite, 0.25#/sx flocele (33 cf). Pkr set @ 4863'.

02-10-93 Precede w/10 bbl gel wtr. Displaced w/20 BW @ 2.5 BPM @ 40 psi. CIBP set @ 5200'. Cmt ret set @ 4900'. Squeeze perf @ 4970' w/130 sx Class "B" 65/35 Poz w/4#/sx gilsonite, 2% calcium chloride (222 cf), tailed w/125 sx Class "B" w/2% calcium chloride (147 cf).

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 2/15/93

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any: