

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Phillips Petroleum Company

3. Address and Telephone No.

5525 Hwy 64 NBU 3004, Farmington, NM 87401 (505) 599-3412

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit H, 2227' FNL & 1186' FEL
Sec. 28, T32N, R7W

5. Lease Designation and Serial No.

SE-078542

6. If Indian, Allottee or Tribe Name

7. Unit or CA, Agreement Designation

San Juan 32-7 Unit

8. Well Name and No.

237

9. API Well No.

30-045-28810

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other As Per NTL-FRA-90-1

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1.

Date: 11-19-92 Time Started: 0945 hrs Time Completed: 1100 hrs

Hole Size 8-3/4" Casing Size 7" Casing Seat 3240 Ft.

Turbo Centralizers at 2550', 2450', 2350'.

Spring Type Centralizers at 2040', 1620', 1010', 550', 100'.

Mud Flush 10 Bbls, Spacer 10 Fresh Water.

Lead Slurry 475 Sx 65/35 Poz w/12% gel, 10% salt, 1/4#/Sk Celloflake

Mid Slurry ---

Tail Slurry 150 Sx Cl G w/2% CaCl2, 1/4#/Sk Celloflake

Displaced Plug with 126 Bbls Fresh Water.

Volume Cement Circulated 45 Bbls/Seals

Average Pressure 700 PSI, Average Rate 5 BPM, Bumped Plug with 1200 PSI.

14. I hereby certify that the foregoing is true and correct

Signed

R. A. Alfred

Title Drilling Supervisor

Date 12-1-92

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

DEC 23 1992

154000

FARMINGTON RESOURCE AREA
BY *SV*