



P.O. Drawer 3337, 700 S. Tucker, Farmington, New Mexico 87499
(505) 327-4961 24-Hour Dispatch (505) 325-6892

HALLWOOD PETROLEUM

NICKLES #11-2

2-9-95

RUN IN HOLE W/5-1/2" RETAINER. SET @ 1790'. PUMP 203 SX BELOW
RETAINER & 22 SX ABOVE RETAINER. LOAD HOLE W/9 LB MUD. PULL
UP TO 1420'. SPOT 17 SX PLUG 1420' - 1270'. PULL UP TO 1150'.
SPOT 20 SX PLUG 1120' - 970'. PULL UP TO 375''. SPOT 15 SX PLUG
375' - 240'. PULL UP TO 60'. CIRCULATE CEMENT TO SURFACE WITH
20 SX. CUT OFF CASING STRINGS & INSTALL DRYHOLE MARKER.

STATE REPRESENTATIVE - JOHNNY ROBINSON

Hallwood Energy Companies

4582 South Ulster Street Parkway Stanford Place III Suite 1700 Post Office Box 378111
Denver, Colorado 80237 (303) 850-7373

February 23, 1995

Mr. Johnny Robinson
State of New Mexico
Oil Conservation Division
1000 Rio Brazos Road
Aztec, New Mexico 87410

RE: Nickles #11-2
Section 11-T31N-R13W
API #30-045-28855

RECEIVED
FEB 27 1995

OIL CON. DIV.
DIST. 3

Dear Mr. Robinson:

Please find enclosed Subsequent Report, Form C-103, for the captioned well. This well was plugged on February 9, 1995.

If you have further questions, please feel free to contact me at (303) 850-6257.

Sincerely,

HALLWOOD PETROLEUM, INC.

Nonya K. Durham

Nonya K. Durham
Production Technician

NKD/jea

Enclosures

NKD95.012

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Submit 3 Copies
Appropriate
District Office

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-045-28855

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Nickles 11

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Hallwood Petroleum, Inc.

8. Well No.

2

3. Address of Operator

P. O. Box 378111, Denver, CO 80237

9. Pool name or Wildcat

Basin Fruitland Coal

4. Well Location

Well Letter L : 1850 Feet From The South Line and 790 Feet From The West Line

Section

11

Township

31N

Range

13W

NMMPM

San Juan

County

10. Elevation (Show whether LF, RKB, RI, GR, etc.)

5702 KB 5690 GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2/9/95

RIH w/5 1/2" retainer. Set @ 1790'. Pump 203 sks below retainer & 22 sks above retainer. Load hole w/9# mud. Pull up to 1420'. Spot 17 sk plug 1420'-1270'. Pull up to 1150'. Spot 20 sk plug 1120'-970'. Pull up to 375'. Spot 15 sk plug 375'-240'. Pull up to 60'. Circulate cement to surface w/20 sks. Cut off csg strings & install dry hole marker.

RECEIVED
FEB 27 1995

OIL CON. DIV.
P.O. BOX 2088

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Nonya K. Durham

TITLE Production Technician

DATE 2/23/95

TYPE OR PRINT NAME

Nonya K. Durham

303-H 11-

TELEPHONE NO 6257

(This space for State Use)

APPROVED BY

James Carlone

TITLE

DM.O.C.D
Deputy Oil & Gas Inspector

DATE 6-14-95

CONDITIONS OF APPROVAL, IF ANY:



P.O. Drawer 3337, 700 S. Tucker, Farmington, New Mexico 87499
(505) 327-4961 24-Hour Dispatch **(505) 325-6892**

HALLWOOD PETROLEUM

NICKLES #11-2

2-9-95

RUN IN HOLE W/5-1/2" RETAINER. SET @ 1790'. PUMP 203 SX BELOW RETAINER & 22 SX ABOVE RETAINER. LOAD HOLE W/9 LB MUD. PULL UP TO 1420'. SPOT 17 SX PLUG 1420' - 1270'. PULL UP TO 1150'. SPOT 20 SX PLUG 1120' - 970'. PULL UP TO 375''. SPOT 15 SX PLUG 375' - 240'. PULL UP TO 60'. CIRCULATE CEMENT TO SURFACE WITH 20 SX. CUT OFF CASING STRINGS & INSTALL DRYHOLE MARKER.

STATE REPRESENTATIVE - JOHNNY ROBINSON