

Texakoma Oil & Gas Corporation
LA PLATA 4 NO. 1 (FEE)
FRUITLAND COAL (BASIN)
SAN JUAN COUNTY, NEW MEXICO
2480' FSL & 2215' FWL OF SEC 4, T 31 N, R 13 W

PROPERTY CODE 15613
 OGRID NO. 022521
 POOL CODE 71629
 API NO. 30-045-29169
 OPERATOR NO. K 0652
 STRAIGHT HOLE
 12 1/4" & 7 7/8" HOLE
 EL. 5909'(GL); 5914'(KB)

18' 16" CONDUCTOR, .325" WALL THICKNESS
 130' 8-5/8", 24 PPF, J-55, STC, R-3, NEW, API, SURFACE CASING.
 CEMENTED W/ 100 SXS STANDARD + 2 % CaCl₂ + 0.25 PPS FLOCELE
 MIXED W/ 5.2 GPS FW @ 15.6 PPG W/A YIELD OF 1.19 CFS. TOC @ SURFACE.
 PLUG BUMPED WITH PSI @ 0:00 P.M. ON 08/00/95.
 WELLHEAD - 8 5/8" SOW X 11" 3M CASING HEAD, TESTED TO 600 PSI.

SPUD -- 2:00 P.M. MST ON 05/16/95.
 TD -- 6:00 P.M. MST ON 05/23/95.

55 JTS - 2 3/8", J-55, 4.7 PPF, EUE, 8rd, R-2, USED, API, TUBING
 1 - 1 1/2" NEW DOWN HOLE PUMP
 71 - 3/4" NEW AND USED GRADE C RODS
 1 - 8' USED PONY ROD

(TOTAL PERFORATIONS -- 162)

RECEIVED
 OCT 12 1995
 OIL CON. DIV.
 OCT. 3

1840'- 42' (2'), 1844' - 50' (6')

1825' = EOT; SN @ 1792 '
 PERFORATIONS @ 1 SPF, 0 DEG PHASE, 19 GPS, 0.45" DIAMETER HOLE SIZE.

1951'- 55' (4'), 1957'- 64' (7'), 1972'- 74' (2')

2003'-06'

PERFORATIONS @ 2 SPF, 180 DEG PHASE, 19 GPS, 0.45" DIAMETER HOLE SIZE.
 5 1/2" HOWCO MULTIPLE STAGE INFLATABLE PACKER COLLAR

2048'- 57' (9'), 2059'- 76' (17'), 2078'- 82' (4') AND
 2086'- 88' (2')

PERFORATIONS @ 4 SPF, 90 DEG PHASE, 19 GPS, 0.45" DIAMETER HOLE SIZE.

2177' PBTD
2180' TD GLM

5 1/2", 15.5 PPF, J-55, LTC, R-3, NEW, API, NSS, PRODUCTION CASING.
 CEMENT: LEAD - 290 SXS HOWCO STANDARD LIGHT + 2% CaCl₂ + 0.25 PPS
 FLOCELE MIXED W/ 9.77 GPS FW @ 12.4 PPG, YIELD OF 1.83 CFS; TAIL- 100
 SXS STANDARD + 0.6 % HALAD-322 MIXED W/ 5.17 GPS FW @ 15.6 PPG,
 YIELD OF 1.18 CFS. TOC @ SUR. CLOSED PORTS/CASING TEST-1300 PSI.

toups
 10/04/95