

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-045-29214
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	7. Lease Name or Unit Agreement Name  Moseley 1
2. Name of Operator Hallwood Petroleum, Inc.	8. Well No. #1
3. Address of Operator P. O. Box 378111, Denver, CO 80237	9. Pool name or Wildcat Basin Fruitland Coal
4. Well Location Unit Letter G : 1590 Feet From The North Line and 2140 Feet From The East Line Section 1 Township 31N Range 13W NMPM San Juan County	10. Elevation (Show whether LF, RKB, RT, GR, etc.) 5780' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG-AND-ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING MAY ☐ 5 1995  
OTHER: OIL CONSERVATION DIVISION ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4/7/95 1. Spud well at 11:30 a.m. on 4/7/95.  
2. Ran 8 jts 24# new 8 5/8" ST&L casing set at 382' KB.
- 4/8/95 3. Pumped 300 sks cmt, circulate 12 bbls cmt to surface.
- 4/10/95 1. Ran 48 jts new 5 1/2" 15.5# csg, set at 2030'.  
2. Cemented with 320 sks of 65:35 Poz w/2% of CC and 70 sks Class "B" with 2% CC.  
3. Circ 20 bbls cmt to surface.  
4. Bump plug, pressure up to 300# and held for 18 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Nonya K. Durham TITLE Production Technician DATE 5/3/95  
TYPE OR PRINT NAME Nonya K. Durham TELEPHONE NO. 303-850-6257

(This space for State Use)

APPROVED BY ORIGINAL SIGNED BY ERNIE BUSCH TITLE REGIONAL & DISTRICT INSPECTOR, OIL & GAS DATE MAY - 5 1995  
CONDITIONS OF APPROVAL, IF ANY: