X

(SUBMIT IN TRIPLICATE)

Jan 19 1 19 14

UNITED STATES

DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Indian	ndian Agency			
Ute	Mountain	Tribal		
Allotte	e			
Lassa	vo 14-20-60)lı-8lı		

C AND DEDODTE ON WELLS

	i d	TOTAL DEPOSIT OF WATER SHIT OFF
NOTICE OF INTENTION TO DRILL		JBSEQUENT REPORT OF WATER SHUT-OFF
IOTICE OF INTENTION TO CHANGE	1 2 110-12-12-1	UBSEQUENT REPORT OF SHOOTING OR APPLIED OF SHOOTING CASING CELLY
IOTICE OF INTENTION TO TEST WA	i \$1	UBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO REDRILL		UBSEQUENT REPORT OF ABANDONMENT OCT 6 105
NOTICE OF INTENTION TO SHOOT O		UPPLEMENTARY WELL HISTORY. 11 8 3504
NOTICE OF INTENTION TO PULL OR		FARMINGTO:
NOTICE OF INTENTION TO ABANDO	N WELL.	FARMINGTON YEW
(INDIC	ATE ABOVE BY CHECK MARK NATURE	E OF REPORT, NOTICE, OR OTHER DATA)
	-	October 3 , 19.
Tribal Vell No is le		line and 1980 ft. from $\binom{E}{W}$ line of sec. 3
NW NE Sec. 30	311 11 (Rang	
(14 Sec. and Sec. No.)	San Juan	New Mexico
Verde-Gallup (Field)	(County or Subd	
tate names of and expected depth	DETAILS (s to objective sands; show sizes, weighing points, and all other in	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, conportant proposed work) —CR. Drilled 12 7 hole to 119 feet.
added with rotary to 0.03 feet 8-5/8" O.D. loium chloride. Com	DETAILS (sto objective sands; show sizes, weighing points, and all other in tools 10:30 a.m. 10-1; t of 8-5/8" 0.D. 1 j. 21:5 set 8 119 feet	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) -58. Drilled 12½ hole to 119 feet. t. 11.86 feet 8-5/8 h 32# and 2 jts. K.B. w/100 sx. regular cement 2% ng down 6;15 p.m. 10-1-58. W.O.C.
added with rotary to 103 feet 8-5/8" O.D.	DETAILS Costs objective sands; show sizes, weiging points, and all other in the collaboration of 8-5/8* 0.D. 1 j.	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) -58. Drilled 12½ hole to 119 feet. t. 11.86 feet 8-5/8 h 32# and 2 jts. K.B. w/100 sx. regular cement 2% ng down 6;15 p.m. 10-1-58. W.O.C.
added with rotary to a 3 jts. 108.89 feet .03 feet 8-5/8" O.D. loium chloride. Com hours. Tested plug	DETAILS Of to objective sands; show sizes, weighing points, and all other in the cols 10:30 a.m. 10-12 to f 8-5/8" 0.D. 1 j. 21 set 9 119 feet sent circulated. Plant w/800 PSI for 30 m	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) -58. Drilled 12½ hole to 119 feet. t. \(\pm\).86 feet 8-5/8 h 32 h and 2 jts. K.B. \(\ps\)/100 sx. regular cement 2% ing down 6 \(\pm\)15 p.m. 10-1-58. W.O.C. OCT 7 1958 OIL CON. COM.
added with rotary to a 3 jts. 108.89 feet .03 feet 8-5/8" O.D. loium ehloride. Can hours. Tested plug	DETAILS Of sto objective sands; show sizes, weiging points, and all other in the state of 8-5/8" O.D. 1 juice of 8	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) =58. Drilled 12½ hole to 119 feet. t. \(\lambda \). 86 feet 8-5/8 h 32 h and 2 jts. t. \(\lambda \). 8. W/100 sx. regular cement 2% and down 6 h \) p.m. 10-1-58. W.O.C. in. Test O.K. OCT 7 1958 OIL CON. COM. ong by the Geological Survey being congrations may be comment.
I understand that this plan of w	DETAILS Cost objective sands; show sizes, weighing points, and all other in the cols 10:30 a.m. 10-1: to 6 8-5/8" 0.D. 1 j. 21: set 2 119 feet sent circulated. Play w/800 PSI for 30 m	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) =58. Drilled 12½ hole to 119 feet. t. \(\lambda \). 86 feet 8-5/8 h 32 h and 2 jts. t. \(\lambda \). 8. W/100 sx. regular cement 2% and down 6 h \) p.m. 10-1-58. W.O.C. in. Test O.K. OCT 7 1958 OIL CON. COM. ong by the Geological Survey being congrations may be comment.
added with rotary to a 3 jts. 108.89 feet .03 feet 8-5/8" O.D. loium ehloride. Company Three Stat	DETAILS Compagnets of the points and sixes, weighing points, and all other in the points of 8-5/8" O.D. 1 just	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) =58. Drilled 12½ hole to 119 feet. t. \(\lambda \). 86 feet 8-5/8 h 32 h and 2 jts. t. \(\lambda \). 8. W/100 sx. regular cement 2% and down 6 h \) p.m. 10-1-58. W.O.C. in. Test O.K. OCT 7 1958 OIL CON. COM. ong by the Geological Survey being congrations may be comment.
added with rotary to a 3 jts. 108.89 feet .03 feet 8-5/8" O.D. loium ehloride. Company Three Stat	DETAILS Cost objective sands; show sizes, weighing points, and all other in the cols 10:30 a.m. 10-1: to 6 8-5/8" 0.D. 1 j. 21: set 2 119 feet sent circulated. Play w/800 PSI for 30 m	of WORK ghts, and lengths of proposed casings; indicate mudding jobs, comportant proposed work) =58. Drilled 12½ hole to 119 feet. t. \(\lambda \). 86 feet 8-5/8 h 32 h and 2 jts. t. \(\lambda \). 8. W/100 sx. regular cement 2% and down 6 h \) p.m. 10-1-58. W.O.C. in. Test O.K. OCT 7 1958 OIL CON. COM. ong by the Geological Survey being congrations may be comment.