

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

14-20-604-62

6. If Indian, Allottee or Tribe Name

Ute Mountain Utes

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ute Indians A # 25 1183

9. API Well No.

3004529417

10. Field and Pool, or Exploratory Area

Ute dome Dakota - 86720

11. County or Parish, State

San Juan New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Nancy I. Whitaker

3. Address and Telephone No.

P.O. Box 800, Denver, Colorado 80201

(303) 830-5039

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

930 FSL 260 FWL Sec. 2 T 31N R 14W UNIT M

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud & Set Report

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU 11/9/96 -- SPUD 8.75" SURFACE HOLE AT 2045 HRS 11/09/96.

DRILLED TO 430'. SET 10 JOINTS OF 7" SURFACE CASING AT 425'. CEMENTED WITH 110 SXS OF CLASS "B" + 3% CACL-2 + .25#/SX FLOCELE + .5% VERSASET. CIRCULATED 8 BBLS TO SURFACE.

PRESSURE TESTED SURFACE CASING TO 2000 PSI. HELD OKAY.

DRILLED 6.25" PRODUCTION HOLE TO 2632'. RAN 63 JTS. 4.5" WC-50 11.6# PRODUCTION CASING AND LANDED AT 2625'. CEMENTED WITH 175 SXS OF 50/50 POZ BLENDED SILICALITE WITH 2% CACL-2 + .4% HALAD-344 + .5% VERSASET + 2% GEL + .25#/SX FLOCELE.. TAILED WITH 50 SXS OF SAME BLEND. CIRCULATED 16 BBLS TO SURFACE.

RIG RELEASED @ 1600 HRS 11/14/96.

NOTE: CBL WILL BE RUN AND SUBMITTED WHEN WELL IS COMPLETED

ACCEPTED FOR RECORD

P. R. Ridd
12/02/96
Bureau of Land Management

14. I hereby certify that the foregoing is true and correct.

Signed

Title

STAFF ASSISTANT

Date

11-19-1996

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.